



1  
2  
3 **REQUEST FOR PROPOSAL**  
4 **I-405, Brickyard to SR 527 Improvement Project**

**Maintenance of Traffic**

5 **2.22 Maintenance of Traffic**

6 **2.22.1 General**

7 The Design-Builder shall perform all Work necessary to meet the requirements  
8 associated with Maintenance of Traffic (MOT), including providing for the safe  
9 and efficient movement of people, goods, and services through and around the  
10 Project, while minimizing adverse impacts to residents, commuters, and  
11 businesses.

12 The Design-Builder shall prepare a Transportation Management Plan (TMP),  
13 including temporary traffic control, Transportation System Management and  
14 Operations, and Public Information Strategies, and shall conduct all on-site  
15 activities relating to traffic maintenance in accordance with this Section.

16 The Design-Builder shall be responsible for coordinating with other projects  
17 within the vicinity of the Project, at a minimum, scheduling of lane closures,  
18 detours, ramp closures, temporary alignments, and staging of construction  
19 activity. Construction activities shall be scheduled to minimize the number of  
20 required closures and to maximize the opportunities available to perform Work  
21 during closures required by other projects. The Design-Builder shall coordinate  
22 and schedule activities to minimize impact on other projects. The Design-Builder  
23 shall coordinate with the Toll Vendor to provide traffic control for their toll  
24 equipment installation and testing activities as provided in the Contract.

25 Refer to Section 2.1, *General Information*, for projects anticipated to be under  
26 construction at the same time as the Project. The Design-Builder shall coordinate  
27 with Local Agencies and Utility companies to identify other projects scheduled  
28 for construction during the duration of the Project.

29 **2.22.2 Mandatory Standards**

30 The following is a list of Mandatory Standards that shall be followed for all  
31 design and construction related to this Section as referenced in Section 2.2,  
32 *Mandatory Standards*.

- 33 1. Special Provisions (Appendix B)
- 34 2. Standard Specifications M 41-10 (Appendix B)
- 35 3. WSDOT *Design Manual* M 22-01 (Appendix D)
- 36 4. Standard Plans M 21-01 (Appendix D)\*
- 37 5. WSDOT *Traffic Manual* M 51-02 (Appendix D)

- 1        6. *WAC 468-95 Washington State Modifications to the Manual on Uniform*  
2        *Traffic Control Devices*, 2009 Edition with Revisions 1 and 2 dated  
3        May 2012 (Appendix D)
- 4        7. *U.S. Access Board Revised Draft Guidelines for Accessible Public Rights-*  
5        *of-Way, November 2005* (Appendix D)
- 6        8. *WSDOT Materials Manual M 46-01* (Appendix D)
- 7        9. *WSDOT Construction Manual M 41-01* (Appendix D)
- 8        10. *WSDOT Sign Fabrication Manual M 55-05* (Appendix D)
- 9        11. *WSDOT Plans Preparation Manual M 22-31* (Appendix D)
- 10       12. *WSDOT Maintenance Manual M 51-01* (Appendix D)
- 11       13. *WSDOT Plan Sheet Library – Work Zone Traffic Control\**
- 12       14. *WSDOT Secretary’s Executive Order E 1060 Speed Limit Reduction in*  
13       *Work Zone* (Appendix T)
- 14       15. *WSDOT Secretary’s Executive Order E 1001 Work Zone Safety and*  
15       *Mobility* (Appendix T)
- 16       16. *King County Parks Requirement for the Sammamish River Trail*  
17       *(Appendix S)*
- 18       17. *FHWA Manual on Uniform Traffic Control Devices for Streets and*  
19       *Highways*, (MUTCD) 2009 Edition with Revisions 1 and 2, dated May 2012  
20       (Appendix D)
- 21       18. *AASHTO Manual for Assessing Safety Hardware (MASH 16), 2016*
- 22       19. *NCHRP Report 350: Devices in Work Zones*, February 2004, Revised  
23       April 2004
- 24       20. *AASHTO A Policy on Design Standards - Interstate System*
- 25       21. *AASHTO A Policy on Geometric Design of Highways and Streets*
- 26       22. *AASHTO LRFD Specifications for Structural Supports for Highway Signs,*  
27       *Luminaires, and Traffic Signals*, 1st Edition, 2015
- 28       23. *AASHTO Roadside Design Guide*, 2010
- 29       24. *Transportation Research Board Highway Capacity Manual, Sixth Edition:*  
30       *A Guide for Multimodal Mobility Analysis*, 2016
- 31       25. *ITE Traffic Control Devices Handbook*
- 32       26. *FHWA Traffic Control Systems Handbook*
- 33       27. *FHWA Traffic Monitoring Guide*
- 34       28. *FHWA Developing and Implementing Transportation Management Plans*  
35       *for Work Zones*
- 36       29. *ITE Traffic Engineering Handbook, 6th Edition*

- 1       30. *ITE Manual of Transportation Engineering Studies*
- 2       31. *ATSSA Quality Guidelines for Work Zone Traffic Control Devices*
- 3       32. *U.S. Access Board ADA Accessibility Guideline*
- 4       33. *FHWA Final Rule on Work Zone Safety and Mobility* (23 CFR Part 630  
5                   Subpart J)

6       \*The plans contained in these Mandatory Standards shall be made Site-specific if  
7                   used for Traffic Control Plans (TCPs). The Plan Sheet Library is located at this  
8                   link: [https://wsdot.wa.gov/engineering-standards/all-manuals-and-standards/plan](https://wsdot.wa.gov/engineering-standards/all-manuals-and-standards/plan-sheet-library/work-zone-typical-traffic-control-plans-tcp)  
9                   sheet-library/work-zone-typical-traffic-control-plans-tcp

10      **2.22.2.1           Conformance to Established Standards**

11       TCPs, signs, and all traffic control devices and procedures furnished or provided  
12                   shall conform to the standards established in the latest WSDOT adopted edition  
13                   (in accordance with WAC 468-95) of the MUTCD, published by the U.S.  
14                   Department of Transportation. Flagging shall also be in accordance with WAC  
15                   296-155-305 and pedestrian traffic control shall also be in accordance with the  
16                   *Public Rights-of-Way Accessibility Guidelines* (PROWAG). Judgment of the  
17                   quality of devices furnished will be based upon *ATSSA Quality Guidelines for*  
18                   *Work Zone Traffic Control Devices*, published by the American Traffic Safety  
19                   Services Association. The condition of signs and traffic control devices shall be  
20                   new or “acceptable” as defined in the *ATSSA Quality Guidelines for Work Zone*  
21                   *Traffic Control Devices* and will be accepted based on a visual inspection by the  
22                   Traffic Control Supervisor (TCS). WSDOT may also identify devices that are  
23                   unacceptable based on the *ATSSA Quality Guidelines for Work Zone Traffic*  
24                   *Control Devices*. The WSDOT Engineer’s decision on the condition of a sign or  
25                   traffic control device will be final. The Design-Builder shall remove and replace a  
26                   sign or traffic control device determined to be unacceptable within 12 hours of  
27                   notification.

28       In addition to the standards of the MUTCD described above, WSDOT enforces  
29                   crashworthiness requirements for most work zone devices. The *MASH 16* has  
30                   superseded the *NCHRP Report 350* as the established requirements for crash  
31                   testing. Temporary traffic control devices manufactured after December 31, 2019,  
32                   shall be compliant with the *MASH 16* crash test requirements, as determined by  
33                   WSDOT, except as follows:

- 34       1. In situations where a *MASH 16* compliant traffic control device does not  
35                   exist and there are no available traffic control devices that were  
36                   manufactured on or before December 31, 2019, then a traffic control device  
37                   manufactured after December 31, 2019, that is compliant with either  
38                   *NCHRP 350* or the 2009 edition of the *AASHTO Manual for Assessing*  
39                   *Safety Hardware (MASH 09)* is allowed for use with approval of the  
40                   WSDOT Engineer.
- 41       2. Temporary traffic control devices that were manufactured on or before  
42                   December 31, 2019 and were successfully tested to *NCHRP 350* or

- 1                    *MASH 09* may continue to be used on WSDOT projects throughout their  
2                    normal service life.
- 3                    3. Small and lightweight channelizing and delineating devices, including  
4                    cones, tubular markers, flexible delineator posts, and plastic drums, shall  
5                    meet the requirements of either *NCHRP 350*, *MASH 09*, or *MASH 16* as  
6                    determined by the manufacturer of the device.
- 7                    4. A determination of crashworthiness for acceptance of trailer-mounted  
8                    devices such as arrow displays, temporary traffic signals, area lighting  
9                    supports, and portable changeable message signs is currently not required.

10                  **2.22.3      *Performance Requirements***

11                  **2.22.3.1      *General***

12                  The Design-Builder shall prepare a TMP including a Traffic Incident  
13                  Management Plan (TIMP) to the WSDOT Engineer for Review and Comment  
14                  and establish a MOT task force prior to any construction activity that may impact  
15                  traffic. The WSDOT Engineer may permit shoulder closures for activities such as  
16                  surveying or environmental and other design-related Work prior to approval of  
17                  the TMP, provided the Design-Builder prepares TCPs in accordance with the  
18                  requirements of this Section. The Design-Builder shall make changes to the TMP  
19                  any time the personnel or conditions of the original TMP or TIMP change. TCPs  
20                  that are within the jurisdiction of the City of Bothell, the City of Woodinville, the  
21                  City of Kirkland, King County, Snohomish County, Community Transit, and  
22                  Sound Transit will require approval from the affected Local Agency.

23                  **2.22.3.2      *Transportation Management Plan***

24                  The Design-Builder shall develop a TMP that includes the items from the  
25                  *Transportation Management Plan Checklist* (Appendix T), and the following  
26                  items:

- 27                  • Descriptions of traffic staging, including conceptual TCPs, to  
28                  accommodate construction staging
- 29                  • Descriptions of the requirements for temporary roadways
- 30                  • Procedures to identify and incorporate the needs of transit operators,  
31                  Utility Owners, schools, and business owners in the Project corridor
- 32                  • Procedures for obtaining concurrence of stakeholders and implementing  
33                  road and lane closures
- 34                  • Processes for developing and obtaining agreement among stakeholders  
35                  for switching procedures
- 36                  • Procedures to identify and incorporate the needs of Local Agencies  
37                  affected by the Work
- 38                  • Procedures to identify and incorporate the needs of Environmental  
39                  Justice (EJ) and Limited English Proficiency (LEP) populations affected  
40                  by the Work

- 1     • Processes for signing transitions during construction from one stage to  
2     the next, and from interim to permanent signing
- 3     • Procedures to identify and incorporate the needs of emergency service  
4     providers, law enforcement entities, and other related corridor users. The  
5     Design-Builder shall also include procedures to ensure all information  
6     required by these agencies to protect the public is made available.
- 7     • Procedures for providing job Site access point for emergency service  
8     provider and law enforcement entities
- 9     • Provisions for incident and emergency response
- 10    • Processes to identify, produce, and receive acceptance for designs of  
11    temporary traffic signals
- 12    • Methods and frequency of inspection and maintenance of all traffic  
13    control throughout the Project limits, including response times to  
14    correct, modify, or implement changes to pavement marking, signing,  
15    temporary lane configurations, and changes in Temporary Concrete  
16    Barrier (TCB) configurations.
- 17    • Descriptions of contact methods, personnel available, and response  
18    times for any conditions requiring attention during off-hours. Include a  
19    Communications Plan to WSDOT Seattle Radio at (206) 440-4490 and  
20    field offices.
- 21    • Identification of measurable limits for the repair and replacement of  
22    traffic control devices, including pavement markings.
- 23    • Processes to determine the need for revised traffic signal timings, and if  
24    revisions are required, detail the procedures for the development,  
25    approval, implementation, testing, and maintenance of all affected  
26    signals.
- 27    • Provisions to maintain existing access to all properties within the Project  
28    limits for the duration of the Project, except as provided by other  
29    Sections
- 30    • Procedures to modify existing access within Project limits
- 31    • Provisions to provide continuous access to established truck routes,  
32    Hazardous Material routes, transit routes, and school bus routes
- 33    • Procedures to modify the plans as needed to adapt to current Project  
34    circumstances
- 35    • Procedures to determine detour routes, and for obtaining acceptance  
36    from all stakeholders for all proposed detour routes. The Design-Builder  
37    shall identify special needs for emergency service providers, transit  
38    service, and truck routes.
- 39    • Procedures to communicate MOT information to the WSDOT's  
40    Communications Team, and to notify the public of MOT issues in  
41    accordance with Section 2.9, *Communications*.

- Procedures to accommodate adjacent projects' TCPs and strategies, if applicable
- Procedures to modify the TCPs when the staging schedule of the Project or any adjacent project changes
- Procedures to coordinate and provide MOT for the Toll Vendor
- Descriptions of traffic staging prior to Toll Infrastructure Completion and Toll Commencement as required in Section 2.26, *Toll Infrastructure*
- Procedures for pavement marking and signing work prior to Toll Commencement
- Descriptions of traffic staging, including conceptual TCPs, after Toll Commencement
- Identify haul routes

### 2.22.3.3 Traffic Incident Management Plan

During construction, MOT will become increasingly sensitive to incidents such as equipment malfunctions, traffic crashes, inclement weather, and special events. The Design-Builder shall prepare and implement a formal TIMP to address how these incidents shall be managed.

#### 2.22.3.3.1 General

The TIMP shall identify methods for immediate incident detection and verification, response, Site management, clearance, and motorist information. The TIMP shall include procedures for interaction with the Northwest Region Traffic Management Center (TMC). In addition, if any Local Agencies along the Project corridor have adopted incident management guidelines, the Design-Builder shall be responsible for coordinating with local policies and procedures.

The TIMP shall reflect proposed construction staging. The Design-Builder shall modify and implement the TIMP in conjunction with planned special events. The TIMP shall include specific time limits for the detection, verification, and classification of incidents, as well as for the dissemination of information about the incidents. The TIMP shall provide a mechanism to review and capture lessons learned from incidents.

The Design-Builder shall coordinate the TIMP development and updates with the Toll Vendor and include the Toll Vendor in TIMP communications.

The TIMP shall identify and provide for the incorporation of design elements to aid incident management, including turn-around for emergency vehicles, emergency access points, incident investigation sites, and signing to help motorists report the location of incidents in the Project.

#### 2.22.3.3.2 Incident Response Team

Immediately upon detection, the Design-Builder shall notify the Traffic Management Center of any vehicles blocking traffic lanes, disabled vehicles on shoulders, or debris on the roadway that may present a traffic hazard to the public

1 or cause traffic to deviate from normal traffic pattern. The Design-Builder will not  
2 be required to provide additional Incident Response Team equipment or  
3 personnel; however, the Design-Builder shall make materials and equipment  
4 available that are on-site as requested by the WSDOT Engineer, WSDOT Incident  
5 Response Team, or the Washington State Patrol (WSP). Removal of animal  
6 carcasses on the roadway shall be in accordance with Section 2.29, *Maintenance*  
7 *During Construction*.

8                           **2.22.3.3.3       Drop Sites**

9 The Design-Builder shall identify a minimum of six drop sites—four on I-405 and  
10 two on SR 522—within the vicinity of the Project where disabled vehicles can be  
11 safely towed off the freeway and motorists can be assisted. A phone and shelter  
12 shall be available at the drop sites for motorists to use. The drop sites may be  
13 retail establishments, such as a hotel, airport, gas station, or repair shop, and shall  
14 be located within 1 mile of the Project limits.

15                           **2.22.3.3.4       Temporary Emergency Turnouts**

16 Temporary emergency turnouts shall be provided on segments where shoulder  
17 widths are less than 8 feet for sections longer than 4,000 feet in length. The  
18 minimum emergency turn-out width shall be 14 feet from the edge line for a  
19 minimum of 150 feet in length, not including transitions. The approach transitions  
20 shall be made at 15:1 (Length:Width) or greater. The departure transitions shall be  
21 made at 25:1 or greater. The emergency turnouts shall have a paved surface and  
22 shall not be subject to ponding or other weather-related conditions that could  
23 render them ineffective. Emergency turnouts shall be located on the right side of  
24 the travel lanes. Advance signing shall be provided 0.25 mile in advance of the  
25 approach transition, and an R8-7 “Emergency Stopping Only” sign shall be  
26 installed adjacent to the emergency turn-out.

27                           **2.22.3.3.5       Emergency Vehicle and Law Enforcement Access**

28 The Design-Builder shall provide coordination with local and regional emergency  
29 service providers, law enforcement entities, and other related corridor users  
30 including timely communication of Lane Closure Plans, Detour Plans, and other  
31 Project elements that may affect the appropriate delivery of time-sensitive  
32 services. Emergency vehicle and law enforcement access shall be maintained  
33 through all nighttime, weekend, and evening closures.

34                           **2.22.3.3.6       Maintain Camera Surveillance**

35 Refer to Section 2.18, *Intelligent Transportation Systems*, for maintenance  
36 requirements of the Closed-Circuit Television system during construction.

37                           **2.22.3.3.7       Variable Message Signs**

38 Refer to Section 2.18, *Intelligent Transportation Systems*, for maintenance  
39 requirements of the existing Variable Message Sign (VMS).

1 Existing VMS approaching the Project on I-405 and adjacent roadways (SR 525,  
2 I-5, SR 527 and SR 522) may be used, with the WSDOT Engineer's concurrence,  
3 to provide motorists with incident and construction-related information prior to  
4 entering the Work zone. VMS shall not be used in lieu of PCMS as the primary  
5 messaging tool. The Design-Builder shall coordinate with the Northwest Region  
6 TMC to provide timely, accurate information regarding planned closures, and  
7 updated traffic and construction information.

8 The Design-Builder shall also provide PCMS to provide information to motorists,  
9 in accordance with this Section.

10 **2.22.3.3.8 Highway Advisory Radio**

11 A portable Highway Advisory Radio (HAR) may be provided and operated by the  
12 WSDOT Engineer. The Design-Builder shall provide and maintain signing for a  
13 portable HAR when requested by the WSDOT Engineer.

14 The Design-Builder shall coordinate with the Northwest Region Construction  
15 Traffic Control Office (CTCO) to provide timely, accurate information regarding  
16 planned closures, and updated traffic and construction information.

17 **2.22.3.3.9 Design-Builder Response Time**

18 The TCS, with the Design-Builder, shall coordinate the resources and equipment  
19 necessary to respond to emergency situations. The resources shall be on-site  
20 within 45 minutes of notification of an emergency situation. The TCS and  
21 Design-Builder shall ensure the support staff is of sufficient size and has the  
22 equipment and materials necessary to respond to issues affecting traffic flow, such  
23 as displaced pre-cast concrete traffic barrier, pothole repair, water on the roadway,  
24 closing lanes, ramps, setting up detours, and other issues that have the potential of  
25 affecting safety of the motoring public.

26 **2.22.3.4 Traffic Control for Toll Vendor**

27 The Design-Builder is advised that WSDOT has a Toll Vendor to establish a Toll  
28 System for the Project. The Design-Builder shall provide access and MOT for the  
29 Toll Vendor during Tolling Equipment installation and testing activities. The  
30 Design-Builder shall provide Design Documents and develop TCPs for the Toll  
31 Vendor for the following work elements:

- 32     • Design and Release for Construction all TCPs required to support the  
33         installation of toll equipment at each toll point. This includes, but is not  
34         limited to, ramp, Express Toll Lanes (ETL), and general-purpose lane(s)  
35         closure plans and detour routes when applicable. See Section 2.26, *Toll*  
36         *Infrastructure*, for additional requirements.
- 37     • The Design-Builder shall provide MOT for the following Toll Vendor  
38         requested closures:
  - 39             ○ 32 ramp closures
  - 40             ○ 7 shoulder closures

- 24 single-lane closures
  - 12 double-lane closures
  - The Design-Builder shall allow up to three traffic control closures during one working shift as requested by the Toll Vendor provided the provisions described in Section 2.22.4.3 are met for each closure type described above. For closures that require two or more lanes to be closed, the Design-Builder shall assume individual lane closures can be sequenced. For bidding purposes, the Design-Builder shall assume sequenced lane closures are counted as one closure. For example, if the ETL lane is closed at 10:00 p.m. and then the adjacent lane is closed at 11:00 p.m., this is counted as one closure (ETL lane plus one adjacent lane).
  - During Toll Equipment installation and testing phases, the Design-Builder shall give priority to the Toll Vendor-requested lane and ramp closures over other lane closures. If proposed lane closures between the Design-Builder and Toll Vendor are in conflict and cannot be resolved, WSDOT reserves the right to approve or reject proposed lane closures.

The Design-Builder shall provide access and traffic control for the Toll Vendor's activities through Toll Commencement. The Toll Vendor will provide traffic control for the Toll Vendor's activities after Toll Commencement of the Project, including lane and shoulder closures. The Design-Builder shall provide access to the Toll Vendor after Toll Commencement if additional lane closures are needed. The Toll Vendor will coordinate all closures through the WSDOT Engineer and the Design-Builder. The Design-Builder shall keep a record of the types of closures and the dates closures were provided to the Toll Vendor.

### 2.22.3.5 Access to Install Transit Components

The Design-Builder shall provide affected Transit Agencies and its vendors access to install BRT Infrastructure in accordance with Section 2.27, *Transit* and Appendix S.

### 2.22.3.6 Maintenance of Traffic Task Force Meetings

The Design-Builder shall establish and chair a MOT task force, which shall include Design-Builder personnel, the WSDOT Engineer, and other WSDOT personnel; the City of Bothell, the City of Woodinville, the City of Kirkland, King County, Snohomish County, Community Transit, Sound Transit; and other agencies that are affected by the TCPs.

The MOT task force will serve as an advisory committee to the Design-Builder. The Design-Builder shall consider all recommendations and input provided by the task force; however, final design and implementation remain the responsibility of the Design-Builder.

The Design-Builder shall schedule and chair MOT task force meetings twice each month from Contract execution to Substantial Completion. The meeting schedule

1 and frequency of meetings may be adjusted upon agreement by the MOT task  
2 force members.

3 The purpose of the meetings shall be to achieve the following:

- 4     • Further refine and develop the TCPs and strategies.  
5     • Review the Design-Builder's MOT details.  
6     • Disseminate Project MOT information to task force meeting attendees.  
7     • Obtain MOT input from task force meeting attendees.  
8     • Develop, refine, and review the TIMP and its implementation.  
9     • Review the TCS log.  
10    • Review MOT traffic operations and discuss signal timing and phasing  
11    improvements to the traffic signal system during all construction stages.  
12    • Identify and coordinate upcoming closures affecting Emergency turn  
13    arounds with Washington State Patrol.  
14    • Identify the need for improvements based on traffic control implemented  
15    previously.  
16    • Discuss comments/complaints about traffic control from the WSDOT  
17    Engineer and the public, and determine how they will be addressed.  
18    • Discuss Work zone related crashes and identify appropriate revisions to  
19    traffic control to prevent future crashes.  
20    • Identify potential haul routes to the task force meeting attendees.  
21    • Review the 3-week look ahead schedule.

22 The Design-Builder shall prepare the agenda, meeting minutes, exhibits, and  
23 Design Plans required for the meetings, and shall invite representatives from  
24 adjacent projects to the meetings.

25    **2.22.4    *Design and Construction Requirements***

26      **2.22.4.1    *Work Zone Traffic Engineering Manager***

27 The Work Zone Traffic Engineering Manager (WTEM) shall be responsible for  
28 ensuring that the design of all elements related to construction staging, Work zone  
29 safety, and Work zone traffic control are completed and all applicable design  
30 requirements are met. The WTEM shall be on-site once a week for the duration of  
31 the construction staging and TCP development unless otherwise approved by the  
32 WSDOT Engineer. The WTEM shall also be available for approval of  
33 modifications to the staging or TCP through Substantial Completion. The WTEM  
34 shall be a Professional Engineer.

35 The WTEM shall have at least 5 years of recent temporary traffic control design,  
36 traffic engineering experience, or both, on complex, urban interstate projects in  
37 design, construction, or both. The WTEM shall understand the concepts of traffic  
38 modeling and have experience designing construction staging, Work zone safety,  
39 and Work zone traffic control.

1        The WTEM shall be responsible for the following design elements including, at a  
2        minimum:

- 3            •      Detours  
4            •      Staging and TCPs  
5            •      Temporary Plans for signals, ITS, lighting, signing, and pavement  
6            markings

7        **2.22.4.2            Traffic Control Plans**

8        The Design-Builder shall prepare documentation to justify all proposed road  
9        closures, detour routes, and reductions in lane storage at traffic signals or ramp  
10       meters. Traffic Analysis shall follow Section 2.21, *Traffic Operations*. The  
11       documentation shall be submitted to the WSDOT Engineer for Review and  
12       Comment with the proposed TCPs.

13       The Design-Builder shall use the procedures in the TMP to develop detailed Site-  
14       specific TCPs that provide for all construction stages and identify opportunities to  
15       expedite construction throughout the course of the Project. The TCPs shall be  
16       prepared under the direction of the Design-Builder's WTEM.

17       All construction signs, flaggers, and other traffic control devices shall be shown  
18       on the TCPs, except for emergency situations. The TCPs shall show locations of  
19       all required advance warning signs, and a safe, protected location for the flagging  
20       station.

21       The TCPs shall show the necessary construction signs, flaggers, uniformed police  
22       officers, and other control devices required to support the Work. The  
23       Design-Builder shall be responsible for submitting proposed TCPs to the WSDOT  
24       Engineer for Review and Comment; releasing the drawings for construction; and  
25       providing copies of the TCPs to the TCS.

26       TCPs shall include, at a minimum, the following items:

- 27            •      Complete plan sheets and details for all stages of construction. This shall  
28            include construction sequencing plans that show the overall approach to  
29            Project staging.  
30            •      The appropriate details when temporary construction of traffic signals,  
31            detour routes, bridges, retaining structures, drainage, and other  
32            miscellaneous construction is required to maintain traffic.  
33            •      Provide applicable closure hours as specified in Appendix T.  
34            •      Roadway plan sheets showing all existing traffic control devices that  
35            will be retained, relocated, or removed; and all temporary traffic control  
36            devices that will be installed, retained, relocated, or removed.  
37            •      The spacing, size, color (legend and background, if applicable), and  
38            quantity of all traffic control devices.  
39            •      Work areas including ingress and egress for construction vehicles.

- 1     • Roadway plan sheets with the location of each sign so it can be easily  
2     read in relation to the roadway and other traffic control devices. A small-  
3     scale layout of each sign shall be shown on the corresponding roadway  
4     plan sheet where the sign is to be placed.
- 5     • Provisions for using temporary barriers and attenuators to satisfy clear  
6     zone requirements, and to protect the traveling public and the  
7     Design-Builder's personnel, including lateral displacement distance  
8     behind barrier.
- 9     • Temporary lighting, signalization, and ITS details, as required.
- 10    • Layouts showing the locations of ground-mounted and overhead signs,  
11    special sign details, clear zones, and structural and foundation  
12    requirements.
- 13    • Drawings on how to fabricate any sign not detailed in the WSDOT *Sign*  
14    *Fabrication Manual* showing dimensions, background color, and legend.
- 15    • Methods for covering, partially covering, or modifying signs when not  
16    applicable to the current phase of construction.
- 17    • Methods for covering, partially covering, or modifying signals when  
18    needed for the current phase of construction.
- 19    • Striping, crosswalks, intersection details, and traffic delineators.
- 20    • Type and location of all pavement markings to be installed, removed, or  
21    renewed for each stage of construction, and locations of the final  
22    pavement markings.
- 23    • Cross-sections covering each significant change in configuration  
24    including, at a minimum, reduction in lane or shoulder widths; reduction  
25    or increase in number of lanes; and changes of lateral barrier placement  
26    or type. Cross-sections shall show lane configuration (including  
27    direction of travel) and widths, shoulder widths, lateral buffer distance  
28    behind barrier, Work areas, and pavement marking type. Cross-sections  
29    shall identify locations of vertical drop-offs or fixed objects adjacent to  
30    the roadway and how they will be protected. Cross-sections shall include  
31    the station limits the section applies to. Cross-sections shall be provided  
32    covering the entire length of the segment included in the TCPs.
- 33    • Typical sections shall identify direction of travel, lane widths, lane type  
34    (general purpose, shoulder, ETL, turn lane, etc.), and number of lanes.
- 35    • Provisions for maintaining toll collection and operations during  
36    construction and phase switching.
- 37    • Access and control of bicyclists and pedestrians including persons with  
38    disabilities in accordance with the Americans with Disabilities Act of  
39    1990 (ADA) through the traffic control zones.
- 40    • TCPs to show how access to transit stops will be maintained.
- 41    • Detail modifications to the TCPs to address wintertime conditions or  
42    periods of suspended Work.

- 1     • A switching procedure for each traffic control stage change identified in  
2     the TCPs. The switching procedure shall include information jointly  
3     determined by the Design-Builder and the WSDOT Engineer, sufficient  
4     to facilitate discussion of each traffic control stage change in the MOT  
5     task force meetings.
- 6     • The TCPs shall be complete. Typical traffic control configurations such  
7     as those found in the MUTCD may be used to assist in developing the  
8     TCPs. Only Site-specific TCPs that have been Released for Construction  
9     (RFC) shall be used by the Design-Builder. Typical plans are not  
10    acceptable unless incorporated as details into the TCPs.
- 11    • Temporary drainage plan and profile sheets showing all existing  
12    drainage that will be retained, relocated, or removed; and all temporary  
13    drainage facilities that will be installed, retained, relocated, or removed  
14    in accordance with Section 2.14, *Stormwater*.

15    The Design-Builder shall maintain an updated log for the approved TCPs in the  
16    document control system. The log shall be available for WSDOT to review at any  
17    time.

#### 18    2.22.4.2.1    *Design Vehicle*

19    The design vehicle and vehicle accommodation shall conform to the requirements  
20    listed in Section 2.11, *Roadway* and Section 2.27, *Transit* for temporary facilities,  
21    including intersections, freeway mainline, freeway ramps, and local roads. See  
22    WSDOT *Design Manual* Chapter 1310 for Accommodating vs Designing for  
23    Vehicles.

24    The Design-Builder shall evaluate traffic patterns and vehicle classifications to  
25    determine an appropriate design vehicle for each Traffic Control Plan. Provisions  
26    for oversized vehicles shall be coordinated with the WSDOT Engineer when  
27    detours or limited vertical clearance are required by the TCPs.

#### 28    2.22.4.3      *Allowable Closures*

29    This Section lists the allowable lane closure hours for the Project. Any restrictions  
30    for roadway segments not listed in this Section require the WSDOT Engineer  
31    approval. No lane closures shall occur outside of the hours specified within this  
32    Section, unless approved in advance and in writing by the WSDOT Engineer. The  
33    Design-Builder shall notify the public in advance of closures. Any required  
34    Traffic Analysis related to closures shall follow Section 2.21, *Traffic Operations*.

35    No temporary lane closures or restrictions, including set-up and removal of traffic  
36    control devices, will be allowed except during the hours permitted by this Section.  
37    In addition, no Work that restricts or interferes with traffic will be allowed from  
38    noon on the day preceding through noon on the day following a holiday or  
39    holiday weekend. Holidays that occur on Friday, Saturday, Sunday, or Monday  
40    are considered a holiday weekend. January 1, the third Monday of January, the  
41    third Monday of February, Memorial Day, June 19, July 4, Labor Day, November  
42    11, Thanksgiving Day, the day after Thanksgiving, and Christmas Day shall be

1                   considered holidays. When any of these holidays fall on a Sunday, the following  
2                   Monday shall be considered a holiday. When any of these holidays fall on a  
3                   Saturday, the preceding Friday shall be considered a holiday.

4                   The Design-Builder shall coordinate their Work activities with other local events  
5                   in the area, so that the events will not be impacted. In addition, road, ramp, and  
6                   lane closures will not be allowed during the following events:

- 7                   • Evergreen State Fair – The Design-Builder shall not close freeway lanes  
8                   on I-405 or SR 522 or the ramps connecting I-405 and SR 522 between  
9                   2 hours prior to and 2 hours after the hours of operation of the Evergreen  
10                   State Fair. The fair generally runs between the last week of August  
11                   through the first week of September.
- 12                   • The Design-Builder shall not close freeway ramps at the I-405/SR 522  
13                   Interchange two hours prior to and two hours after events with an  
14                   attendance over 2,500 during a Chateau Ste. Michelle concert or event.
- 15                   • The Design-Builder shall identify any organized event, such as 5k runs,  
16                   half-marathons, marathons, and bicycle rides, on the Sammamish River  
17                   Trail or North Creek Trail within the work zone and shall adjust closure  
18                   times to minimize impacts to these events. No trail closures or trail  
19                   detours shall be implemented on event days.
- 20                   • Scheduled roadway closures of SR 520 between I-405 and I-5
- 21                   • Scheduled roadway closures of I-90 between I-405 and I-5
- 22                   • Annual Seafair Hydroplane Race weekend from noon Friday to  
23                   8:00 p.m. Sunday
- 24                   • The Design-Builder shall also identify any major event, such as a  
25                   sporting event or any combination of events, with an anticipated  
26                   combined attendance over 30,000 and shall adjust closure times to  
27                   minimize the impact to traffic in accordance with Section 2.9,  
28                   *Communications*. No traffic restrictions shall be implemented between  
29                   2 hours prior to and 2 hours after the end of events.
- 30                   • Additional limitations shall be placed on traffic restrictions such as lane  
31                   closures, ramp closures, and detours during the holiday period from  
32                   November 15 of each year through January 2 of the following year. No  
33                   shifts to traffic patterns of lane configurations, city street closures, or  
34                   extended ramp closures shall be made during the holiday period unless  
35                   approved by the WSDOT Engineer.

36                   The Design-Builder shall accommodate passage of superloads (as defined by the  
37                   WSDOT Commercial Vehicle Services), wide loads or other permit loads through  
38                   the temporary traffic control area and exceptions to the allowable lane closures  
39                   may be necessary to do so. In addition, the Design-Builder shall coordinate with  
40                   adjacent concurrent projects to provide continuity in the lane configurations.

41                   WSDOT reserves the right to not approve traffic restrictions and freeway  
42                   closures.

1        Liquidated damages will be assessed for failure to complete Work and open all  
2        lanes and ramps to traffic by the specified times, in accordance with Section 1-08  
3        of the *General Provisions*.

4                    **2.22.4.3.1        Lane Closures**

5        The Design-Builder shall maintain the existing lane channelization configuration,  
6        except at the I-405/SR 522 Interchange, at all times outside of the allowable  
7        closures described in this Section, unless otherwise permitted in this Section. At  
8        the I-405/SR 522 Interchange, the Design-Builder shall maintain the minimum  
9        required channelization at all times outside the allowable closures described in  
10      this Section, unless otherwise permitted in this Section.

11      See Appendix T for a list of allowable lane closures on I-405, SR 527, SR 522,  
12      and other local streets and trails in the Project vicinity.

13      The Design-Builder shall coordinate with WSDOT to develop allowable mainline  
14      closure hours for use after Toll Commencement. These hours will supersede and  
15      may differ from those provided in this Section and Appendix T. WSDOT will use  
16      traffic data from 12 months prior to Toll Commencement to generate mainline  
17      closure hours for use after Toll Commencement. After Toll Commencement,  
18      vehicles will not be allowed to cross the double white lines between the ETL and  
19      general purpose lanes.

20                   **2.22.4.3.2        Full Freeway, Highway, and Roadway Closures**

21      The Design-Builder will be allowed to close all lanes of mainline freeways,  
22      highways, and roadways on I-405 and SR 522 in accordance with this Section and  
23      Appendix T upon Written notification to the WSDOT Engineer and upon prior  
24      approval by the WSDOT Engineer and all Local Agencies impacted by the detour  
25      routes.

26      The Design-Builder shall provide Written notification to the WSDOT Engineer  
27      and the affected local agencies of the planned closure, including the date and time  
28      of the closure, the Work activities scheduled for Work preceding the full closure,  
29      and the applicable traffic control, at least 60 Calendar Days in advance of the full  
30      freeways, highways, and roadways closure. A traffic analysis shall be conducted  
31      for all full freeway mainline closures as described in Section 2.21, *Traffic*  
32      *Operations*, and shall be provided to WSDOT and affected agencies as part of this  
33      notification.

34      The Design-Builder shall submit the scheduled closure to the WSDOT Engineer  
35      for Review and Comment at least 14 Calendar Days prior to the date on which the  
36      closure is scheduled. WSDOT will provide a response acknowledging the closure  
37      request within 2 business days. All freeways, highways, and roadways closures  
38      not confirmed by the Design-Builder as scheduled shall be canceled.

39      Detour routes shall be provided by the Design-Builder for all freeways, highways,  
40      and roadways closures. Detours shall be approved by impacted Local Agencies a  
41      minimum of 30 Calendar Days prior to implementing the closure. The  
42      Design-Builder shall coordinate the closure with nearby projects and WSDOT

1 Maintenance activities to ensure no conflicting Work activities are planned,  
2 including ramp or roadway closures that have conflicting or overlapping detours.

3 Roadway closures, detours, and alternate routes must be analyzed by WSDOT for  
4 disproportionate impacts to EJ and LEP communities, in accordance with  
5 Section 2.8, *Environmental*. If an EJ or LEP community is identified along a  
6 proposed route and will be disproportionately impacted, appropriate mitigation  
7 must be coordinated between WSDOT Communications and the Design Builder.  
8 When additional changes are made to the route, it should be evaluated to  
9 determine if the detour adds congestion, noise or creates safety issues for adjacent  
10 residences and businesses and/or adds considerably longer distance to access  
11 residences/businesses that may affect low income and minority population.  
12 WSDOT will work with local agencies and conduct public outreach as necessary,  
13 to ensure that the proposed route will not have a disproportionately high and  
14 adverse effect on EJ or LEP populations.

15 The Communications Plan must include appropriate accommodations for  
16 identified populations and businesses.

17 A submittal that does not conform to the Contract Time limits, is incomplete,  
18 unintelligible, or includes inaccurate information, will be returned to the  
19 Design-Builder for correction. The Design-Builder will be notified promptly of a  
20 disapproved closure or a closure that will require coordination with other parties,  
21 including EJ and LEP, as a condition of approval.

22 Detour routes proposed by the Design-Builder shall be evaluated to determine if  
23 the detour adds congestion, noise or creates safety issues for adjacent residences  
24 and businesses and/or adds considerably longer distance to access  
25 residences/businesses that may affect low income and minority population,  
26 including EJ and LEP populations.

27 All detours shall be in place, including all advance-signing, prior to closure of the  
28 freeways, highways, and roadways.

29 Full closure of the freeways and highways shall require WSP enforcement as part  
30 of the traffic control strategy and use of WSP be reflected on the TCPs.

31 The Design-Builder shall complete all Work within the specified closure times  
32 prior to opening the freeways, highways, and roadways to traffic.

33 Advance notification, public notification, and signing requirements shall be in  
34 accordance with this Section and Section 2.9, *Communications*.

35 The Design-Builder shall provide the WSDOT Engineer with a Contingency Plan  
36 for re-opening closed freeways, highways, and roadways to public traffic in the  
37 event of equipment breakdown, shortage of materials, lack of production of  
38 materials, or other production failure; or when it becomes necessary to re-open  
39 the closure for use by public traffic. The Design-Builder shall furnish an hour-by-  
40 hour schedule of all Work activities to be performed during the full freeways,  
41 highways, and roadways closure, including the Work activities scheduled for  
42 Work preceding the full closure. The Design-Builder shall also furnish a  
43 Contingency Plan for this closure including re-opening lanes for general public

1 traffic. The Contingency Plan and its acceptance by the WSDOT Engineer shall  
2 not relieve the Design-Builder from the liquidated damages as specified in this  
3 Section and Section 1-08.9 of the *General Provisions*.

4 **2.22.4.3.3      *Entrance and Exit Ramp Closures***

5 The Design-Builder will be allowed to close ramps during the hours listed in  
6 Appendix T. The Design-Builder shall maintain the existing ramp configurations,  
7 or the ramp configurations provided in the minimum required configuration plan  
8 as provided in Appendix T, at all times outside of the allowable closures  
9 described in this Section, unless otherwise permitted in this Section. Refer to  
10 Section 1-08 of the *General Provisions* for liquidated damages associated with  
11 failure to fully re-open ramps by the opening time given in the table below. If two  
12 or more ramps within the Project limits are planned to be closed concurrently, and  
13 the closed ramps have overlapping detours, the Design-Builder shall conduct an  
14 analysis of the detour routes in accordance with Section 2.21, *Traffic Operations*,  
15 and submit it to the WSDOT Engineer. If overlapping detours are determined to  
16 be unacceptable by the WSDOT Engineer, then only one ramp closure will be  
17 allowed. Closure durations shall be reduced based on the results of this analysis.

18 The Design-Builder will be allowed to close ramps upon Written notification to  
19 WSDOT and upon prior approval by the WSDOT Engineer and all affected Local  
20 Agencies, provided that the requirements for ramp access are satisfied, and  
21 provided that the closure is shown on an RFC TCPs. Consecutive off-ramps or  
22 consecutive on-ramps shall not be closed concurrently unless approved by the  
23 WSDOT Engineer.

24 The Design-Builder shall provide a Written ramp closure schedule to the WSDOT  
25 Engineer at least 14 Calendar Days in advance of a ramp closure. The schedule  
26 shall show the locations and times of all ramp closures and the allowable closure  
27 time limits specified in the Contract. A schedule that does not conform to the  
28 Contract Time limits, is incomplete, unintelligible, or includes inaccurate  
29 information, will be returned to the Design-Builder for correction. The  
30 Design-Builder will be notified promptly of any disapproved closures or any  
31 closure that will require coordination with other parties as a condition of approval.  
32 Requests for ramp closures made less than 14 Calendar Days in advance will not  
33 be approved.

34 The Design-Builder shall confirm all scheduled closures with the WSDOT  
35 Engineer at least 7 Calendar Days prior to the date on which the ramp closure is  
36 scheduled. All ramp closures not confirmed by the Design-Builder as scheduled  
37 shall be canceled. Confirmed ramp closures that are canceled for unsuitable  
38 weather may be rescheduled for the next allowable day.

39 The Design-Builder shall provide detour routes for ramp closures and all roadway  
40 closures. Detours shall be approved by impacted Local Agencies a minimum of  
41 14 Calendar Days prior to implementing the closure. All detours shall be in place,  
42 including all signing, prior to closure of the ramp. If more than one ramp or

1                   roadway will be closed at the same time, all detour routes shall be shown on the  
2                   same plan.

3                   The Design-Builder shall coordinate ramp closures with nearby projects in  
4                   accordance with Section 2.1, *General Information*, to ensure consecutive ramps or  
5                   off-ramps are not closed simultaneously or result in conflicting or overlapping  
6                   detours.

7                   The Design-Builder shall complete all ramp Work within the specified allowable  
8                   closure times prior to opening the ramps to traffic.

9                   **2.22.4.3.4           Allowable Shoulder Closures**

10                  Shoulder closures will be permitted during the allowable lane closure hours. In  
11                  addition, temporary mainline shoulder closures will be permitted in accordance  
12                  with the RFC TCPs as follows:

- 13                  •           Between 9:00 a.m. and 2:00 p.m. daily, including weekends, in  
14                  accordance with the TCPs

15                  Shoulders that are adjacent to a closed lane shall be closed. Metered ramp  
16                  shoulder lanes shall not be closed unless the ramp is fully closed.

17                  **2.22.4.4           Traffic Operations During Construction**

18                  The Design-Builder shall notify WSDOT's Seattle Radio at (206) 440-4490 when  
19                  setting up and removing all lane, shoulder, and roadway closures.

20                  The Design-Builder shall use protective vehicles with warning beacons for  
21                  protection of Work zones on roadways with a posted speed limits less than  
22                  45 mph and Transportable Attenuators (TAs) for protection of Work zones on  
23                  roadways with a posted speed limit equal to or greater than 45 mph.

24                  Haul routes shall not use private roadways located within the project limits.

25                  **2.22.4.4.1           Mainline During Construction**

26                  Existing shoulders can be used as traveled lane or Work zone truck access in  
27                  accordance with Section 2.7, *Pavement*.

28                  There may be existing facilities in the existing roadway shoulder that may not be  
29                  adequate for traveled lane or Work zone truck access operations. These may  
30                  include, at a minimum, drainage structures, junction boxes, cable and drainage  
31                  vaults, manholes, pull boxes, and the lids for these facilities. Prior to using an  
32                  existing shoulder as all or part of the Traveled Way, the Design-Builder shall  
33                  inspect all existing facilities within the roadway shoulder which may be used as  
34                  traveled lane or Work zone truck access and remediate any existing facilities  
35                  within the roadway shoulder which are not adequate to support sustained traffic.  
36                  All damaged facilities shall be replaced at the Design-Builder's expense.

37                  Mainline and Auxiliary Lanes shall be a minimum of 11 feet wide and shall not  
38                  exceed 14 feet wide unless otherwise specified. Shoulders shall be a minimum of  
39                  5 feet wide where adequate room is available.

1 When shoulders are less than 5 feet wide, construction signs shall be barrier-  
2 mounted or placed behind the barrier at an elevated height to ensure visibility  
3 from a height of 3 feet from the roadway surface.

4 Tripod-mounted signs are allowed when shoulders are greater than 5 feet wide.

5 The Design-Builder shall not clip construction signs. When placement of a sign  
6 edge is within 2 feet of the Traveled Way, the Design-Builder may implement one  
7 of the following strategies:

- 8 • Use a sign smaller than the typical 48- by 48-inch size (roughly  
9 67 inches wide diagonally).
- 10 • Omit the sign and provide additional advance warning at other locations.
- 11 • Design special rectangular signs to convey the same message but with a  
12 reduced width.

13 When shoulders are greater than 10 feet wide, the Design-Builder shall place  
14 drums at 80-foot spacing, 10 feet from the edge line, supplemented by a minimum  
15 of two transverse devices at 500-foot spacing.

16 The Design-Builder shall provide an 8-foot right shoulder/distress lane, when  
17 feasible. Each shoulder shall be a minimum of 2 feet wide and shall be paved.  
18 Wider shoulders may be required to accommodate the necessary sight distance.

19 The Design-Builder shall design any temporary construction or widening to  
20 withstand the anticipated traffic volumes and loadings during the applicable stage  
21 of the Project.

22 Mainline general purpose lanes in the same direction of travel shall not be split or  
23 separated.

24 Design-Builder shall maintain access at all times from SR 522 to the WSDOT  
25 Maintenance Stockpile sites under the I-405/SR 522 Interchange.

26 Once one or more signals on SR 522 are operational, the Design-Builder shall  
27 maintain the proposed minimum configuration on SR 522 between the Campus  
28 Way intersection and the northbound I-405 to eastbound SR 522 off-ramp at all  
29 times outside the allowable closures as shown in Appendix T.

30 The Design-Builder shall maintain the existing number of ETLs and toll access  
31 points in each direction on I-405 at all times prior to toll commencement within  
32 the Project limits. Refer to Section 2.26, *Toll Infrastructure*, for additional toll  
33 system rollout requirements. After toll commencement, the Design-Builder shall  
34 maintain the number of ETLs and access points as defined in the basic  
35 configuration.

36 The Design-Builder shall maintain the existing buffer between the ETL lanes and  
37 the adjacent general purpose lanes. All locations where the existing buffer width  
38 cannot be maintained, a minimum a 2-foot buffer shall be provided with a double  
39 solid white line separation, except at existing ETL access locations, during all  
40 construction stages of the Project.

1 ETL lane shifts shall not be allowed within 50 feet upstream and downstream of  
2 existing toll gantries and the existing edge line and buffer striping shall be  
3 maintained as to not disrupt tolling operations. After replacement Toll Points are  
4 operational and toll collection has shifted to the new toll point, refer to  
5 Section 2.26, *Toll Infrastructure*, for provisions on lane shifts.

6 Disruptions to the toll system that impact revenue collection shall be subject to  
7 liquidated damages as specified in this Section and Section 1-08.9 of the *General*  
8 *Provisions*.

#### 9                           **2.22.4.4.1.1                   Design Criteria**

10 The design speed for temporary conditions shall not be less than the posted speed  
11 on I-405, and on SR 522 between milepost (MP) 10.70 and 11.90. The design  
12 speed for temporary conditions shall not be less than 35 mph on SR 522 between  
13 Kaysner Way to MP 10.70. All mainline shifting tapers and lane closure tapers  
14 shall be in conformance with standards provided in the latest version of the  
15 MUTCD.

#### 16                           **2.22.4.4.1.2                   Temporary Lane Closures**

17 The Design-Builder shall provide Written notification to the WSDOT Engineer  
18 and all affected Local Agencies a minimum of 7 Calendar Days prior to each  
19 closure. Each lane closure shall have one sequential arrow board per closed lane,  
20 as part of the traffic control layout. No closures shall be scheduled until the TCPs  
21 are RFC.

22 For lane closures longer than 500 feet, the Design-Builder shall use a minimum of  
23 two transverse devices in the closed lane at 500-foot spacing.

#### 24                           **2.22.4.4.1.3                   Law Enforcement**

25 Law enforcement shall be provided for rolling slowdowns, full freeway closures,  
26 and to control intersections when traffic signals are temporarily turned off. Law  
27 enforcement for the Work zone shall be included in the Proposal Price.

#### 28                           **2.22.4.4.1.4                   Sequential Arrow Displays**

29 Each vehicle used to place, maintain, or remove components of a traffic control  
30 system on multi-lane highways shall be equipped with a sequential arrow display  
31 that shall be in operation when the vehicle is in use. Vehicles equipped with  
32 sequential arrow displays not involved in placing, maintaining, or removing  
33 components when operated within a stationary-type lane closure shall display  
34 only the four-corner flash caution mode. The operator of the vehicle shall control  
35 the arrow display while the vehicle is in motion. Sequential arrow displays used in  
36 moving lane closures shall be truck-mounted. This requirement applies to all  
37 vehicles placing, maintaining, and removing traffic control devices, including  
38 concrete barrier trailers and "cherry pickers".

## 2.22.4.4.1.5 Advance Signing

The Design-Builder shall furnish and install four G24-501 (modified) signs with the Project hotline phone number within the Project limits: One sign in the northbound direction and one in southbound direction of I-405 near where traffic enters the Project, and one sign in the westbound direction and one sign in the eastbound direction of SR 522 near where traffic enters the Project. The signs shall be installed within 30 Calendar Days of the date the Contract is executed, and prior to all other construction activity on the Project. The signs shall remain in place until Physical Completion and be maintained by the Design-Builder. Coordination with nearby projects may be required for placement of the signs.

WSDOT will supply the Project identification sign. The Design-Builder shall be responsible for coordination, transportation, and installation of the sign, including supplying the posts for the sign and placards with the Project amount and Design-Builder's name. Refer to the *Project Identification Sign Detail* (Appendix W). These signs shall be located a minimum of 800 feet away from any guide sign and motorist information signs.

The Design-Builder shall pick up the sign at the address below, and shall coordinate the receipt of the Project identification signs by contacting:

Scott Hammersmith  
WSDOT Traffic Maintenance, Building 12  
6431 Corson Avenue South  
Seattle, WA 98105-3145  
Phone: (206) 768-5882

If it is necessary to relocate advance signing for any reason, the Design-Builder shall be responsible for relocation.

#### **2.22.4.4.2 Ramps During Construction**

## 2.22.4.4.2.1 Design Criteria

The Design-Builder shall provide acceleration and deceleration lanes to ensure vehicles are within 10 mph of the mainline speed at the point they must merge or diverge from mainline lanes. Exit speeds shall be posted for all ramps. For ramps where the design speed during construction is reduced from existing conditions, black on orange construction signs shall be used for the exit speed signs.

The NE 160th Street on-ramp to southbound I-405 shall maintain the existing two-lane general purpose and HOV configuration during construction or until the in-line freeway transit station at Brickyard is operational.

After the I-405 northbound to SR 522 westbound flyover ramp is demolished, the Design-Builder shall maintain at least two lanes on the I-405 southbound to SR 522 westbound ramp at all times during construction.

The number of lanes and lane configurations shall equal or exceed the existing configuration or the minimum required configuration during construction of the SR 522 interchange provided in Appendix T. Adequate storage for queuing and

1       throughput volumes at traffic signals and ramp meters shall be maintained. Ramp  
2       meters shall be maintained on all on-ramps and the existing storage shall be  
3       considered the minimum. On-ramps shall have adequate ramp storage and shall  
4       meter the appropriate number of lanes based on the criteria provided in the  
5       WSDOT *Northwest Region ITS Design Requirements* during all construction  
6       phases. Ramp meters shall not operate with two vehicles per green indication.  
7       Lanes shall be a minimum of 11 feet wide on entrance and exit ramps. Paved  
8       shoulders shall be provided on both sides of each ramp and shall be a minimum of  
9       2 feet wide. Wider ramp widths than these minimums shall be required where  
10      necessary to satisfy AASHTO design widths for turning roadways and horizontal  
11      stopping sight distances, and to accommodate WB-67 on General Purpose ramps  
12      and Bus-45 with bike rack on ETL ramps for design vehicle tracking. Refer to the  
13      WSDOT *Design Manual*. All exit ramp tapers shall use a desirable taper rate of  
14      20:1, and a minimum taper rate of 15:1.

15      Turning movements at the ramp terminals shall be designed to accommodate a  
16      WB-67 design vehicle on General Purpose ramps and a Bus-45 with bike rack  
17      design vehicle on ETL ramps.

18      **2.22.4.4.3            *Local Roads During Construction***

19      The Design-Builder shall maintain the existing local street configuration at all  
20      times outside the allowable closures from the Local Agencies, unless otherwise  
21      permitted in this Section.

22      All TCPs affecting local roads shall meet the minimum channelization  
23      requirements and allowable closure hours as identified in Appendix T, and shall  
24      follow the requirements of each Local Agency impacted. The Design-Builder  
25      shall be responsible for submitting plans and obtaining approvals from the Local  
26      Agencies for each planned closure and detour route. Allowable closure hours for  
27      lane and roadway closures on local roads shall be approved by the corresponding  
28      Local Agency. The Design-Builder shall coordinate with City of Bothell, City of  
29      Woodinville, City of Kirkland, King County, Snohomish County, Sound Transit,  
30      and Community Transit regarding concurrent construction work along city cross-  
31      streets that may be affected by traffic control for the Project; see *Right of Way*  
32      *Use Permits*, if any.

33      The Design-Builder shall provide Written notice to the WSDOT Engineer and the  
34      affected Local Agencies a minimum of 30 Calendar Days prior to restricting local  
35      traffic. The Design-Builder shall be responsible for obtaining approval for each  
36      planned closure from WSDOT and the Local Agencies affected by the Work. The  
37      Design-Builder shall be responsible for obtaining all necessary permits from  
38      Local Agencies associated with lane closures on local streets. The Design-Builder  
39      shall maintain access to all affected businesses and residences during the lane  
40      closures. The Design-Builder shall maintain access to all affected residences on  
41      NE 155th Street during full closures.

### **2.22.4.4.3.1 Design Criteria**

The design speed of all local roads during construction shall be the existing posted speed limit. Any reduction from the existing posted speed limit shall be identified in the TMP and requires approval by the corresponding Local Agency.

The existing number of lanes, intersection turn pockets, and intersection signal phasing shall be maintained at all times except as approved by the WSDOT Engineer and the affected Local Agency. All lanes for local roads shall be a minimum of 11 feet wide, measured to the front of gutter, unless the existing lane width is less than 11 feet, in which case the lane shall not be less than the existing width.

## 2.22.4.4.3.2 Detours

All detours shall be in place, including all signing, prior to closure of any road. Detours using local roads shall follow traffic control permit requirements for each Local Agency impacted. Detours shall not be permitted on private roadways and the Design-Builder shall provide appropriate signing restricting the use of such private roadways as detours.

Detour signing for interstate/freeway, roadway, or entrance ramp closures shall include specific route shield, cardinal direction, and arrow of appropriate orientation comprised on one sign of either 48- by 48-inch (posted speeds of 45 mph or greater) or 36- by 36-inch (below 45 mph) in size.

The Design-Builder shall identify all bus routes, including school bus routes, which may be affected by the detour; and shall coordinate with the bus agency regarding impacts to the schedule and location of the bus stops.

### **2.22.4.4.3.3 Park and Rides During Construction**

The Canyon Park and Brickyard Park and Ride facilities shall remain fully operational and maintain their existing configuration and transit services at all times during construction except as allowed in Appendix S and Appendix T.

The Canyon Park and Brickyard Park and Ride facilities work shall conform to the Bothell Municipal Code, and Transit requirements outlined Section 2.27, *Transit*.

#### **2.22.4.4.4 *Temporary Guardrail, Barrier Attenuators, and Glare Screen***

## **2.22.4.4.1 Vehicle Protection**

The Design-Builder shall be responsible for using temporary guardrail, barrier, and attenuators to protect the traveling public from the following:

- Fixed objects within the clear zone
  - Drop-offs as required by this Section
  - Slopes steeper than 4H:1V (Horizontal:Vertical)

1                           **2.22.4.4.4.2                   Barrier and Glare Screen**

2                           Opposing traffic lanes of mainline I-405 and SR 522 shall be separated by  
3                           permanent barrier or TCB in accordance with WSDOT design requirements.

4                           TCB placed along the edge of a bridge structure shall be anchored.

5                           The end of TCB shall not be placed within the clear zone of approaching traffic  
6                           unless an appropriate attenuator is used. Refer to the WSDOT *Design Manual* for  
7                           minimum taper rates and additional details.

8                           The Design-Builder shall provide a lateral displacement distance behind all  
9                           barriers (including TCB) equal to or greater than the longitudinal barrier  
10                          deflection shown in Exhibit 1610-3 of the WSDOT *Design Manual*. The lateral  
11                          displacement area shall be kept clear of fixed objects and shall not be used as a  
12                          Work area.

13                          When mainline median crossovers are used, temporary glare screen, in  
14                          accordance with Sections 8-25 and 9-16 of the Standard Specifications, using slats  
15                          shall be placed on top of the median TCB to reduce the headlight glare of  
16                          approaching vehicles. All concrete barriers shall have reflectorized barrier  
17                          delineators of the appropriate color with 20-foot maximum spacing. The barrier  
18                          delineators shall be side-mounted.

19                           **2.22.4.4.5                   Pedestrian and Bicycle Access During Construction**

20                          The Design-Builder shall maintain existing pedestrian access on all sidewalks,  
21                          transit facilities, and intersections, except as permitted in this Section and  
22                          Appendix T. The Design-Builder shall also maintain safe pedestrian access and  
23                          passage for all pedestrian facilities. Pedestrian sidewalks and paths shall be  
24                          maintained and continue to conform to the Public Rights of Way Accessibility  
25                          Guidelines (PROWAG) requirements ([www.access-board.gov/prowag](http://www.access-board.gov/prowag)).

26                          Occupational safety regulations that apply to the Project limits shall also be  
27                          considered the minimum standard for personal safety to pedestrians. If Work will  
28                          be performed over any pedestrian and bicycle routes, temporary lighted covered  
29                          walkways shall be provided to protect pedestrians and bicyclists from overhead  
30                          hazards.

31                          When the Design-Builder allows Work areas to encroach upon a sidewalk or  
32                          crosswalk area and a minimum clear width of 48 inches cannot be maintained for  
33                          pedestrian use, an alternative accessible pedestrian route shall be provided.  
34                          Separation of pedestrians from the Work area and vehicular traffic is required.

35                          Protective barricades, fencing, and bridges, together with warning and guidance  
36                          devices and signs, shall be used so that the passageway for pedestrians is safe,  
37                          well defined, and accessible. Whenever pedestrian walkways are provided across  
38                          excavations, they shall be provided with handrails in accordance with ADA  
39                          requirements. Footbridges shall be designed in accordance with AASHTO LRFD  
40                          specifications; have a slip-resistant coating; and be free of cracks, holes, and  
41                          irregularities that could cause tripping. Ramps with a maximum slope of  
42                          8.3 percent shall be provided at the entrance and exit of all raised footbridges. The

1 maximum cross slope shall be 2 percent. When the existing facility is illuminated  
2 or TCPs require illumination, illumination shall be provided during the hours of  
3 darkness. Retroreflective delineation, with or without illumination, shall be  
4 provided during hours of darkness.

5 Where accessible pedestrian routes are allowed to be closed by the  
6 Design-Builder during construction, an alternate accessible pedestrian route shall  
7 be provided that complies with the MUTCD, the PROWAG requirements, and  
8 this Section. The alternate accessible pedestrian route shall not have abrupt  
9 changes in grade or terrain. Pedestrian channelizing devices shall be detectable to  
10 pedestrians who have visual disabilities and a handrail meeting PROWAG  
11 requirements. Where it is necessary to divert pedestrians into the roadway,  
12 barricading or channelizing devices shall be provided to separate the pedestrian  
13 route from the adjacent vehicular traffic lane. Barricading or channelizing devices  
14 used to separate pedestrian and vehicular traffic shall be crashworthy in  
15 accordance with the WSDOT *Design Manual* Chapter 1610, and, when struck by  
16 vehicles, present a minimum threat to pedestrians, workers, and occupants of  
17 impacting vehicles. At no time shall pedestrians be diverted into a portion of the  
18 street used concurrently by moving vehicular traffic.

19 The Design-Builder shall maintain an ADA accessible pedestrian access, per  
20 PROWAG requirements, across I-405 at all times to and from the Canyon Park  
21 Park and Ride and transit stops located on the I-405 ramps, except per the  
22 allowable closures listed in Appendix S and T. The crossing shall have lighting  
23 and be protected from work zone vehicles, equipment, and other hazardous  
24 activities at all times. The Design-Builder shall restrict pedestrians from deviating  
25 from pedestrian facilities in to work zone areas by utilizing barricades,  
26 channelizing devices, flaggers, or Design-Builder traffic control personnel.

27 The Design-Builder shall not park motor vehicles or construction equipment on  
28 an open pedestrian sidewalk or path, or use an open pedestrian sidewalk or path  
29 for loading operations, stockpiling of materials, or allowing demolished or spoil  
30 materials to be deposited on the surface of an open pedestrian sidewalk or path.  
31 Any surface of a pedestrian sidewalk or path affected by the Work shall be  
32 restored to meet ADA requirements prior to re-opening to pedestrian traffic. The  
33 pedestrian sidewalk or path surface shall be swept or washed free of debris  
34 including, at a minimum, mud, gravel, grease, and excavated, spoiled, or  
35 stockpiled materials.

36 Pedestrian and bicycle routes shall not be closed except during full closures of the  
37 adjacent roadways or trails. During full closures of the adjacent roadways or  
38 trails, a Pedestrian and Bicycle Access Plan shall be implemented with a  
39 minimum of 14 Calendar Days advance notice provided to all pedestrians and  
40 bicyclists. The Design-Builder shall notify the affected local agencies prior to the  
41 closure of any trails. A Pedestrian and Bicycle Access Plan shall not require  
42 pedestrians or bicyclists to travel more than 0.5 miles longer than the  
43 preconstruction distance, with the exception of allowable full closures of trails as  
44 identified in Appendix T. Advance notice shall consist of signs located at the  
45 construction limits and all accesses serving the affected area; and public

1 notification in accordance with Section 2.9, *Communications*. All access closures  
2 and Pedestrian and Bicycle Access Plans shall be shown in the TCPs. All detours  
3 and Work Sites shall be signed in accordance with MUTCD, ADA requirements,  
4 and this Section. Refer to Chapters 1510 and 1520 of the WSDOT *Design Manual*  
5 and the *King County Parks Requirement for the Sammamish River Trail*  
6 (Appendix S) for Sammamish River Trail closures.

7 **2.22.4.5 Public Convenience and Safety**

8 **2.22.4.5.1 Construction Under Traffic**

9 The Design-Builder shall conduct all operations with the least possible  
10 obstruction and inconvenience to the public. The Design-Builder shall not have  
11 under construction a greater length or amount of Work than can be prosecuted  
12 properly with due regard to the rights of the public. To the extent possible, the  
13 Design-Builder shall finish each section of Work before commencing Work on  
14 the next section. The Design-Builder shall enter interstate highways only through  
15 legal movements from existing roads, streets, and other access points specifically  
16 permitted by the Contract.

17 In order to minimize public traffic disruption, the Design-Builder shall permit  
18 traffic to pass through the Work zone with the least possible inconvenience or  
19 delay. The Design-Builder shall maintain existing roads and streets within the  
20 Project limits, keeping them open, and in a good, clean, safe condition at all times  
21 except at allowable closure times per this Section. Deficiencies caused by the  
22 Design-Builder's operations shall be repaired at the Design-Builder's expense.  
23 Except where noted in this Section and Section 2.29, *Maintenance During*  
24 *Construction*, deficiencies not caused by the Design-Builder's operations shall be  
25 repaired by the Design-Builder, when directed by the WSDOT Engineer, at  
26 WSDOT's expense. Pothole damage shall be repaired by the Design-Builder at  
27 the Design-Builder's expense. The Design-Builder shall also maintain roads and  
28 streets adjacent to the Project limits when affected by the Design-Builder's  
29 operations. Snow and ice control will be performed in accordance with  
30 Section 2.29, *Maintenance During Construction*. The Design-Builder shall  
31 perform the following:

- 32 • Remove or repair any condition resulting from the Work that might  
33 impede traffic or create a hazard.
- 34 • Maintain operation of traffic signals and highway lighting systems as the  
35 Work proceeds.
- 36 • Maintain the striping on the roadway.
- 37 • Maintain existing permanent signing. Sign repairs will be at WSDOT's  
38 expense, except those damaged due to the Design-Builder's operations.
- 39 • Keep drainage structures clean to allow for free flow of water.

40 To protect the rights of abutting property owners, the Design-Builder shall  
41 perform the following:

- 1     • Conduct the construction so that abutting property owners are  
2     inconvenienced as little as possible.
- 3     • Provide and maintain transit access to transit facilities. Transit only  
4     facilities shall remain open except as allowed in Appendix S and  
5     Appendix T.
- 6     • Maintain access to driveways, houses, and buildings within the Project  
7     limits.
- 8     • Provide temporary approaches to crossing or intersecting roads and keep  
9     these approaches in good condition.
- 10    • Provide another access before closing an existing access whenever the  
11    Contract calls for removing and replacing an abutting owner's access.

12    When traffic must pass through grading areas to access private property, the  
13    Design-Builder shall perform the following:

- 14    • Make cuts and fills that provide a reasonably smooth, even roadbed.
- 15    • In advance of other grading Work, place enough fill at all culverts and  
16    bridges to permit traffic to cross.
- 17    • After rough grading or placement of any subsequent layers, prepare the  
18    final roadbed to a smooth, even surface free of humps and dips, suitable  
19    for use by public traffic.
- 20    • Settle dust with water or other dust palliative.

21    If grading Work is on or next to a roadway in use, the Design-Builder shall finish  
22    the grade immediately after rough grading and place surfacing materials as the  
23    Work progresses.

24    Where planing is performed, live traffic will be allowed to drive on the ground  
25    surface for a maximum of 5 Calendar Days before an overlay is required in the  
26    planed section. Planing shall be performed either parallel or perpendicular to the  
27    current channelization.

28    The Design-Builder shall conduct all operations to minimize any drop-offs  
29    (abrupt changes in roadway elevation) left exposed to traffic during non-working  
30    hours. Grinding shall not be allowed after the final paving lift is completed. Drop-  
31    offs left exposed to traffic during nonworking hours shall be protected as follows  
32    and shall be shown in the RFC TCP submitted in accordance with this Section:

- 33    1. Drop-offs up to 0.20 foot may remain exposed with appropriate warning  
34    signs alerting motorists of the condition. The drop-offs shall not remain  
35    open for more than 3 Calendar Days.
- 36    2. Drop-offs more than 0.20 foot that are in the Traveled Way or Auxiliary  
37    Lane will not be allowed unless protected with appropriate warning signs  
38    and further protected as indicated in 3b or 3c below.
- 39    3. Drop-offs more than 0.20 foot, but no more than 0.50 foot, that are not  
40    within the Traveled Way or Auxiliary Lanes shall be protected with

appropriate warning signs and further protected by using one of the following:

- a. A wedge of compacted stable material placed at a slope of 4H:1V or flatter.
  - b. Channelizing devices (Type I barricades, plastic safety drums, or other devices 36 inches or more in height) placed along the traffic side of the drop-off and a new edge of pavement stripes placed a minimum of 3 feet from the drop-off. The maximum spacing between the devices in feet shall be the posted speed in mph. Pavement drop-off warning signs shall be placed in advance and throughout the drop-off treatment.
  - c. A TCB or other approved barrier installed on the traffic side of the drop-off with a new edge line placed a minimum of 2 feet from the traffic face of the barrier. The barrier shall have a lateral offset from the edge of the drop-off to the back of the barrier as follows:
    - i. A minimum offset of 3 feet for temporary Type F or Type 2 concrete barrier when unanchored.
    - ii. A minimum offset of 1-foot for temporary Type F or Type 2 concrete barrier when anchored on hot mix asphalt pavement as shown on WSDOT Standard Plan C-60.10 or K80.35.
    - iii. A minimum offset of 1-foot for temporary Type F concrete barrier when anchored on cement concrete pavement as shown on WSDOT Standard Plan C-60.10
    - iv. A minimum offset of 9 inches for temporary Type F or Type 2 concrete barrier when anchored on cement concrete pavement and/or concrete bridge decks as shown on WSDOT Standard Plan K-80.35
    - v. A minimum offset of 6 inches or 9 inches for temporary Type F or Type 2 narrow base concrete barrier when anchored on cement concrete pavement and concrete bridge decks as shown on WSDOT Standard Plan K-80.37.
    - vi. A minimum offset following manufacturer recommendations for temporary steel barrier when not anchored; or when anchored on hot mix asphalt pavement, cement concrete pavement, or concrete bridge decks.
    - vii. A minimum offset as directed by the WSDOT Engineer for any barrier type or configuration not shown in this Section.

An approved terminal, flare, or impact attenuator shall be required at the approach end of the barrier run and is required at the trailing end of a barrier run in two-way operations when shown on the RFC TCPs or as directed by the WSDOT Engineer. For night use, the barrier shall have standard delineation such as paint, reflective tape, lane markers, or warning lights.

Drop-offs more than 0.50 foot not within the Traveled Way or Auxiliary Lane shall be protected with appropriate warning signs and further protected as indicated in 3a, 3b, or 3c above, if all of the following conditions are met:

- 1        a. The drop-off is less than 2 feet.
- 2        b. The total length throughout the Project is less than 1 mile.
- 3        c. The drop-off does not remain for more than 3 Calendar Days.
- 4        d. The drop-off is not present on any holiday or holiday weekend described  
5                in this Section.
- 6        e. The drop-off is only on one side of the roadway.
- 7        5. Drop-offs more than 0.50 foot that are not within the Traveled Way or  
8                Auxiliary Lane and are not otherwise accounted for by No. 4 above, shall be  
9                protected with appropriate warning signs, and further protected as indicated  
10              in 3a or 3c above.
- 11        6. Open trenches within the Traveled Way or Auxiliary Lane shall have a  
12              steel-plate cover placed and anchored over them. A wedge of suitable  
13              material, if required, shall be placed for a smooth transition between the  
14              pavement and the steel plate. Warning signs shall be used to alert motorists  
15              of the presence of the steel plates.

#### 16        2.22.4.5.2            *Work Zone Clear Zone*

17        The Work Zone Clear Zone (WZCZ) applies during working and non-working  
18              hours. The WZCZ applies only to temporary roadside objects introduced by the  
19              Design-Builder's operations and does not apply to preexisting conditions or  
20              permanent Work. Those work operations that are actively in progress shall be in  
21              accordance with TCPs and these Technical Requirements.

22        During nonworking hours equipment or materials shall not be within the WZCA  
23              unless they are protected by permanent guardrail or temporary concrete barrier.  
24              The use of temporary concrete barrier shall be permitted only if the WSDOT  
25              Engineer approves the installation and location.

26        During actual hours of active construction Work, unless protected as described  
27              above, only materials absolutely necessary for construction shall be allowed  
28              within the WZCZ; and only construction vehicles absolutely necessary for  
29              construction shall be allowed within the WZCZ or allowed to stop or park on the  
30              shoulder of the roadway. No equipment shall be stored within the WZCZ between  
31              shifts of active construction Work.

32        The Design-Builder's nonessential vehicles and employee's private vehicles shall  
33              not be permitted to park within the WZCZ at any time, unless protected as  
34              described above.

35        Deviation from the above requirements shall not occur unless the Design-Builder  
36              has requested the deviation in writing and the WSDOT Engineer has provided  
37              Written approval.

38        Minimum WZCZ distances are measured from the edge of the Traveled Way, and  
39              shall be determined as follows:

### Minimum Work Zone Clear Zone Distance

Posted Speed	Distance from Traveled Way (feet)
35 mph or less	10
40 mph	15
45 to 50 mph	20
55 to 60 mph	30
65 mph or greater	35

1 Construction vehicles using a closed traffic lane shall travel only in the normal  
2 direction of traffic flow, unless expressly allowed in the RFC TCPs. Construction  
3 vehicles shall be equipped with flashing or rotating amber lights.

4 Work over an open lane of traffic shall not be allowed, unless a plan for the  
5 protection of the traveling public from debris falling onto the Traveled Way is  
6 approved by the Engineer of Record. This protection shall remain in place during  
7 construction and shall meet minimum vertical clearance for the highway.

#### 2.22.4.5.2.1 Controlled Access

9 The Design-Builder shall not be allowed any special access, egress, including  
10 leaving the roadway shoulder to enter the Work area, or breaks in limited access,  
11 other than normal legal movements or movements as approved by the WSDOT  
12 Engineer. The Design-Builder shall be allowed short-duration shoulder stops in  
13 the Work area, using light vehicles properly equipped with amber warning lights.

14 All ingress and egress to the Work area shall be shown on Site-specific RFC  
15 TCPs. The Design-Builder shall provide appropriate warning signs and traffic  
16 control devices when vehicles will be departing or entering highway and city  
17 streets. Ingress and egress to the Work area shall not be located at a gore.

18 The Design-Builder shall close a lane of traffic in locations where the length and  
19 width of the shoulder is not adequate for construction vehicles to decelerate from  
20 departing the mainline traffic to enter the Work area or to accelerate from exiting  
21 the Work area to merge with the mainline traffic. The design speed for departing  
22 and merging into a mainline shall not be less than 10 mph below the design speed  
23 of the mainline. Access for large construction vehicles to and from an open lane,  
24 meeting the criteria above, shall only be between the hours of 9:00 a.m. and  
25 3:00 p.m. daily, and during the lane closure hours described in this Section. Light  
26 vehicles properly equipped with amber warning lights shall be allowed access to  
27 the Work area to and from an open lane, meeting the criteria above, at all times.

28 Lane closures and ingress and egress to the Work area shall be restricted to the  
29 hours described in this Section, unless otherwise approved by the WSDOT  
30 Engineer.

1 Access to the Work area from adjacent properties outside of the Right of Way  
2 shall be in accordance with Section 1-07.16(1) of the *General Provisions*.

3           Design-Builder vehicles or equipment, marked or personal, shall not use private  
4           roadways to travel to or from and/or access the Work area.

5 For an approved break in limited access, the Design-Builder shall prohibit  
6 unauthorized use of the access from adjacent property. Access from outside the  
7 limited access lines shall be closed by use of a locked gate when the access point  
8 is not being used.

9 The access location shall not adversely affect wetlands or other sensitive areas.  
10 Airborne particulates created as a result of using the access shall be effectively  
11 controlled. The continuity of the existing drainage system shall be maintained  
12 throughout the access Site.

13 At the Completion of the Project, the Design-Builder shall restore the area of the  
14 access Site to its original, pre-Contract, condition. Any damage to the Traveled  
15 Way, shoulders, Auxiliary Lanes, side slopes or other areas caused by the access  
16 shall be repaired. All Work to comply with this provision or to build, maintain,  
17 provide erosion control, control airborne particulates, ensure that drainage  
18 continues throughout the access Site, provide traffic control, when necessary,  
19 remove the temporary access, and restore the surrounding area when no longer  
20 required for use is the responsibility of the Design-Builder. The Design-Builder  
21 shall include all related costs in the Proposal Price of the Contract.

## 2.22.4.5.2.2 Work During Hours of Darkness

23 Work during hours of darkness may be required for the Project. The  
24 Design-Builder shall obtain any required noise variance or exemption for such  
25 Work. The Design-Builder shall, at no additional cost to WSDOT, make all  
26 arrangements for operations during hours of darkness.

27 Flagger station illumination shall meet the requirements of the MUTCD and these  
28 Technical Requirements. The Design-Builder shall provide portable lighting  
29 equipment capable of sufficiently illuminating a flagger and their station without  
30 creating glare for oncoming motorists yet will meet the mobility requirements of  
31 the operation. The lighting stations shall be located on the same side of the  
32 roadway as the flagger and aimed either parallel or perpendicular to the traveled  
33 lanes to minimize glare. The lighting devices shall be located 5 to 10 feet from the  
34 edge of the travel lane with a mounting height of 15 to 25 feet above the ground.  
35 The flagger shall be visible and discernable as a flagger from a distance of  
36 1,000 feet.

37       Lighting for construction activity shall be directed away from maintained traffic  
38       to minimize glare to motorists.

39 Refer to this Section and Section 1-07 of the *General Provisions* for additional  
40 requirements.

## 2.22.4.5.2.3 Signs and Traffic Control Devices

All signs and traffic control devices for lane and roadway closures shall be installed only during the hours specified in this Section. If placed earlier than the specified hours of closure, the construction signs shall be turned or covered so as not to be visible to motorists.

## 2.22.4.5.2.4 Advance Notification

The Design-Builder shall submit TCPs for lane and shoulder closure requests in writing to the WSDOT Engineer 14 Calendar Days in advance of the proposed closure.

## 2.22.4.5.2.5 Hour Adjustment

If the permitted closure hours adversely affect traffic, causing queues that extend beyond 1.5 miles or delay traffic for longer than 15 minutes for any lane or total roadway closure, the Design-Builder shall evaluate the Contract hours and recommend new hours to the WSDOT Engineer for Review and Comment.

## 2.22.4.5.2.6 Public Notification

The Design-Builder shall furnish and install information signs that provide advance notification of ramp and roadway closures a minimum of 7 Calendar Days prior to the scheduled closure. The signs shall have a black legend on a white reflective background. Sign locations, messages, letter sizes, and sign sizes shall be shown in the TCPs. For ramp and local road closures, PCMS shall be used to supplement the required signs. The Design-Builder shall notify the WSP, local fire departments, police departments, city engineering departments, public transit agencies, and the affected school districts in writing a minimum of 7 Calendar Days prior to scheduled closures. The Design-Builder shall provide these notifications to WSDOT.

## 2.22.4.5.2.7 Mast Arm Erection and Traffic Block Allowance

During erection of mast arm assemblies, the Design-Builder may, with the prior authorization from the WSDOT Engineer, block all traffic for intervals of a maximum of 5 minutes between midnight and 4:00 a.m. These 5-minute blockages shall be separated by an interval long enough to allow the delayed vehicles to clear.

### **2.22.4.5.3 Construction and Maintenance of Detours**

Unless otherwise approved, the Design-Builder shall maintain two-way traffic during construction. The Design-Builder shall build, maintain in a safe condition, keep open to traffic, and remove when no longer needed, the following:

- Detours and detour bridges that will accommodate traffic diverted from the roadway or bridge during construction
  - Detour crossings of intersecting highways

1                   •     Temporary approaches

2     The Design-Builder shall pay all costs to build, maintain, and remove any other  
3     detours, whether built for the Design-Builder's convenience or to facilitate  
4     construction operations. Any detour proposed by the Design-Builder shall  
5     conform to the requirements of the Contract. Surfacing and paving shall be  
6     consistent with traffic requirements.

7     Upon failure of the Design-Builder to immediately provide, maintain, or remove  
8     detours or detour bridges, the WSDOT Engineer may, without further notice to  
9     the Design-Builder or the Surety, perform any of the above and deduct all of the  
10    costs from any payments due or coming due to the Design-Builder.

11                   **2.22.4.6     Construction Requirements**

12                   **2.22.4.6.1     General**

13     The Design-Builder shall plan, manage, supervise, and perform all temporary  
14     traffic control activities required to support the Work using labor, equipment, and  
15     materials provided by the Design-Builder (except when such labor, equipment, or  
16     materials are to be provided by WSDOT specifically identified herein).

17     The Design-Builder shall be responsible for all MOT starting at 12:01 a.m. on the  
18     day following Notice to Proceed (NTP). The temporary traffic control devices,  
19     including temporary signal systems, shall be continually and adequately  
20     monitored and maintained to ensure proper placement and working order, and to  
21     ensure the safe and efficient flow of all traffic through and adjacent to the Project.  
22     Such responsibility and maintenance shall continue until 11:59 p.m. on the day of  
23     Completion of the Project. The WSDOT Engineer may, in writing, temporarily  
24     suspend such responsibility in conjunction with an official suspension for weather  
25     or other reasons.

26                   **2.22.4.6.2     Materials**

27     All materials shall meet the requirements of Section 9-35 of the Standard  
28     Specifications. Additionally, all materials shall conform to the requirements of the  
29     Special Provisions.

30                   **2.22.4.6.3     Traffic Control During Construction**

31     The Design-Builder shall provide flaggers and all other personnel required for  
32     traffic control activities, unless specified in the Contract as being provided by  
33     WSDOT.

34     The Design-Builder shall perform all procedures necessary to support the Work.

35     The Design-Builder shall provide signs and other traffic control devices not  
36     otherwise specified in the Contract as being provided by WSDOT. The  
37     Design-Builder shall erect and maintain all construction signs, warning signs,  
38     detour signs, and other traffic control devices necessary to warn and protect the  
39     public at all times from injury or damage as a result of the Design-Builder's

1 operations which may occur on or adjacent to highways, roads, or streets. No  
2 Work shall be done on or adjacent to the roadway until all necessary signs and  
3 traffic control devices are in place.

4 The traffic control resources and activities described shall be used for the safety  
5 of the public, the Design-Builder's employees, and WSDOT personnel; and to  
6 facilitate the movement of the traveling public. Traffic control resources and  
7 activities may be used for the separation or merging of public and construction  
8 traffic when such use is in accordance with the RFC TCPs.

9 Upon failure of the Design-Builder to immediately provide flaggers; erect,  
10 maintain, and remove signs; or provide, erect, maintain, and remove other traffic  
11 control devices when requested to do so by the WSDOT Engineer, the WSDOT  
12 Engineer may, without further notice to the Design-Builder or the Surety, perform  
13 any of the above and deduct all of the costs from any payments due or coming due  
14 to the Design-Builder.

15 The Design-Builder shall be responsible for providing adequate labor, sufficient  
16 signs, and other traffic control devices; and for performing traffic control  
17 procedures needed for the protection of the Work and the public at all times  
18 regardless of whether or not the labor, devices, or procedures have been ordered  
19 by the WSDOT Engineer, provided by the WSDOT Engineer, or paid for by  
20 WSDOT.

21 When performing Work, the Design-Builder's equipment shall follow normal and  
22 legal traffic movements. The Design-Builder's ingress and egress of the Work  
23 area shall be accomplished with as little disruption to traffic as possible. Traffic  
24 control devices shall be removed by picking up the devices in a reverse sequence  
25 to that used for installation. This may require backing up through the Work area.  
26 When located behind barrier or at other locations shown on RFC TCPs,  
27 equipment may operate in a direction opposite to adjacent traffic.

28 Under the Contract, the Design-Builder is responsible for all traffic control, and  
29 any such participation by law enforcement personnel in traffic control activities  
30 shall be preceded by an agreement. Nothing in the Contract is intended to create  
31 an entitlement, on the part of the Design-Builder, to the services or participation  
32 of the law enforcement organization.

33                   **2.22.4.6.4           *Signing, Pavement Markings, and Traffic Control***  
34                   ***Devices During Construction***

35 The Design-Builder shall inspect all signing (existing and temporary) daily noting  
36 damaged signs, misplaced signs, and graffiti affecting legibility of the signs.  
37 Every detour route shall be driven hourly to ensure all detour signing is in place.  
38 Signing for detours shall be covered or removed when detours are not in use. The  
39 Design-Builder shall provide a schedule for repairing, cleaning, or replacing  
40 signs; procedures shall address rectifying incorrect or misleading signing that may  
41 present a hazard to road users.

42 The Design-Builder shall ensure there are no conflicting or misleading signs due  
43 to adjacent projects. The Design-Builder shall coordinate with adjacent projects

1 and relocate signs as required to avoid conflicting information. Temporary  
2 pavement markings shall be installed in accordance with Sections 8-23 and 9-34  
3 of the Standard Specifications.

4 The Design-Builder shall ensure temporary pavement markings do not conflict  
5 with existing pavement markings including recessed and raised markings. If a  
6 conflict occurs with existing recessed pavement markings the Design-Builder  
7 shall remove the recessed pavement markings by filling the recess with hot mix  
8 asphalt for prelevel in accordance with Section 5-04 of the Standard  
9 Specifications.

10 The Design-Builder shall use temporary removable tape for temporary pavement  
11 marking configurations in areas that will not be ground or overlaid. Refer to  
12 Section 2.20, *Pavement Marking*, for tape specification. Temporary pavement  
13 markings shall be identified on the TCPs and the TMP. If paint or temporary  
14 removable tape is used for temporary markings that will remain in place for  
15 48 hours or longer, the markings shall be supplemented with Type 2 Raised  
16 Pavement Marker (RPM) installed at 40-foot spacing and in accordance with  
17 Standard Plan M-20.30. In areas where Type 2 RPM are used to supplement  
18 temporary removable tape, the adhesive for the Type 2 RPM shall be butyl  
19 rubber. The Design-Builder shall follow all manufacturers' preparation and  
20 application procedures for this product. In areas that will be ground or overlaid,  
21 Standard Plan M-20.50 shall be used for striping configurations lasting more than  
22 30 Calendar Days.

23 The Design-Builder shall not use a grinder to remove painted markings. For  
24 removal of plastic markings, grinding will be allowed down to the pavement  
25 surface.

26 The Design-Builder shall use a shot blasting machine with a minimum 3-foot-  
27 wide cleaning path to remove the ghost stripes and texture the entire width of the  
28 traveled way. Ghost striping is defined as the shadow or scarring on the pavement  
29 surface where pavement markings have been removed.

30 All pavement markings that are not in use for the current MOT phase shall be  
31 removed by the Design-Builder unless the pavement markings are behind a  
32 barrier. Pavement markings to be removed shall be obliterated until they are  
33 unidentifiable as a pavement marking. The pavement marking removal shall be  
34 considered adequate when any remaining pavement marking material is not  
35 visible to a person with normal vision observing the removal area from a standing  
36 position looking 40 feet ahead. In no case shall the pavement marking removal or  
37 the shot blasting remove more than 0.0625-inch of existing pavement. The shot  
38 blasting of the traveled way shall be feathered into the existing shoulders. The  
39 Design-Builder shall ensure that the sections of traveled way that receive shot  
40 blasting will continue to adequately allow water to drain to the shoulders and  
41 there will be no areas where ponding of water remains. Sand or other material  
42 deposited on the pavement surface as a result of removing pavement markings  
43 shall be removed as the Work progresses to avoid hazardous conditions.

44 Accumulation of sand or other material which might interfere with drainage will

1 not be permitted. Temporary paint on the final pavement surface shall be placed  
2 only in the final pavement marking configuration.

3 The Design-Builder shall inspect all pavement markings daily. The  
4 Design-Builder shall provide a schedule for replacing damaged pavement  
5 markings and establish minimum replacement time frames based on the degree of  
6 degradation. If missing or damaged pavement markings present a hazardous  
7 condition, WSDOT may require the Design-Builder to close lanes or replace the  
8 pavement markings within 24 hours.

9 The Design-Builder shall clean or replace all pavement markings when they  
10 become damaged or lose reflectivity.

11 The Design-Builder shall replace or clean temporary pavement markings  
12 whenever the reflectance of the markings has deteriorated to less than  
13 100 mcd/m<sup>2</sup>/lux. The Design-Builder shall perform the required tests monthly, at  
14 1-mile intervals or at specific locations requested by the WSDOT Engineer.

15 As each construction phase is completed, the Design-Builder shall install the  
16 signing and pavement markings required to safely open the road to traffic. This  
17 Work shall be completed on or before the date of opening. Overhead signs except  
18 exit only signs may be temporarily ground-mounted at the Design-Builder's  
19 expense.

20 The Design-Builder shall have adequate spare sections of temporary barrier and  
21 the necessary equipment on-site to replace and repair temporary barrier within  
22 4 hours of identification by or notice given to the Design-Builder of damaged  
23 barrier. This requirement shall include replacement of impact attenuators.  
24 Temporary traffic control shall be set up immediately upon notice of damage to  
25 ensure vehicle safety.

#### 26 **2.22.4.6.5      *Temporary Signalization***

27 This Section applies to new temporary signals necessary for detour routes or other  
28 construction staging, if any. Any modifications to existing traffic signals must be  
29 shown in the TCPs and approved by the operating agency. Modifications  
30 proposed for signal timing or staging shall be supported with a traffic analysis  
31 based on the requirements in Section 2.21, *Traffic Operations*, and coordinated  
32 with and approved by the operating agency. A traffic signal warrant analysis may  
33 be required for approval.

#### 34 **2.22.4.6.5.1      *Temporary Signal Requirements***

35 The Design-Builder shall furnish and install all required materials for the  
36 temporary signalization. The Design-Builder shall provide vehicle detection  
37 methods to optimize all temporary signal system installations. The Design-Builder  
38 may use Type 3 induction loops or video image detection for temporary signal  
39 installations.

## 2.22.4.6.5.2 WSDOT Inspection

The Design-Builder shall provide a minimum of 7 Calendar Days' notice to the WSDOT Engineer prior to implementing temporary signalization. The WSDOT Engineer will perform the final electrical inspection and acceptance of temporary signal systems in accordance with WAC 296-46B, *Electrical Safety Standards, Administration, and Installation*. When signals are owned and operated by other Local Agencies, the Design-Builder shall follow that jurisdiction's requirements.

### 2.22.4.6.5.3 Signal Turn-On

The Design-Builder shall secure and pay for the services of a law enforcement agency to perform traffic control while the traffic signal is being placed into service. Appropriate signing shall be installed by the Design-Builder in advance of signal turn-on. The Design-Builder shall request a timeframe for signal turn-on from the WSDOT Engineer. The request for the signal turn-on shall be submitted 14 days in advance for the desired date, and approval by the WSDOT Engineer shall be obtained at least seven days prior to actual turn-on date.

## 2.22.4.6.5.4 Operation and Maintenance

The Design-Builder shall develop Timing and Signal Coordination Plans and staging for the temporary signal operation. Timing and Signal Coordination Plans will be reviewed during each construction phase and updated if changes to the number of lanes, intersection spacing, signal phasing, or clearance interval are required. WSDOT or the operating agency will enter the timing parameters into the signal controller. The Design-Builder may be allowed to enter the timing parameters into the signal controller with the approval or at the request of the WSDOT Engineer or the operating agency.

WSDOT or the operating agency will operate the temporary signal systems once the signal is turned on and operational. Maintenance of the temporary signal system shall be the Design-Builder's responsibility. The Design-Builder shall remove all temporary signal systems upon completion and operation of the new permanent signal systems.

#### **2.22.4.6.6      *Temporary Illumination***

The Design-Builder shall evaluate the lighting values of the existing illumination in relation to the temporary configuration to determine if the existing illumination provides the required illumination values. If the required illumination values are not satisfied, the Design-Builder shall provide temporary illumination satisfying the “construction lanes and detours” light level and uniformity ratios in accordance with the WSDOT *Design Manual*.

Where temporary illumination is required, the existing illumination system shall not be removed until the temporary system is operational. Only lighting equipment no longer needed for illumination of the roadway shall be removed.

1       The Design-Builder shall provide temporary lighting satisfying the “construction  
2       lanes and detours” light level and uniformity ratios when existing lighting must be  
3       removed or disconnected, and new lighting is not in operation.

4 The Design-Builder shall provide temporary lighting for all intersections where  
5 traffic control devices are in place. The temporary lighting shall satisfy the greater  
6 of the “construction lanes and detours” or the specific intersection light level and  
7 uniformity ratios.

8           Temporary lighting is required when an obstruction (such as a new bridge) is  
9           placed over an area requiring illumination and shall be installed prior to placing  
10          the obstruction.

11           The Design-Builder shall provide temporary lighting satisfying the “construction  
12           lanes and detours” light level.

13        In addition to the requirements of the WSDOT *Design Manual*, the  
14        Design-Builder shall provide temporary lighting satisfying the “construction lanes  
15        and detours” light level and uniformity ratios for temporary channelization or  
16        traffic control.

17 Portable light stands shall not be used for temporary roadway lighting.

18 The Design-Builder shall provide temporary illumination satisfying the “required  
19 illumination” described in the WSDOT *Design Manual*. Temporary illumination  
20 shall be in place and in operation prior to implementing the TCPs which require  
21 the temporary illumination.

## 2.22.4.6.6.1 General

23 At a minimum, the Design-Builder shall perform the following:

- Design Temporary Lighting Plans.
  - Maintain current levels of roadway illumination for all roadway segments, pedestrian bridges, and intersections that are currently lit.
  - Provide all materials and equipment for temporary lighting installations.
  - In the clear zone, provide only lighting units that are breakaway or protected from crash potential.
  - Provide maintenance for the temporary lighting system. Any damage to the existing illumination system shall be repaired prior to hours of darkness on the following day.

33       Temporary illumination shall be provided in accordance with the requirements for  
34       construction lanes and detours in the *WSDOT Design Manual*.

## 2.22.4.6.6.2 Timber Light Standards

36 Timber light standards may be used for temporary lighting where breakaway or  
37 slip bases are not required. Timber light standards must be outside of the clear  
38 zone or protected by barrier.

1                   **2.22.4.7           Traffic Control Personnel**

2                   The Design-Builder shall plan, conduct, and safely perform the Work. The  
3                   Design-Builder shall manage temporary traffic control.

4                   The Design-Builder shall provide all personnel for flagging; execution of all  
5                   procedures related to temporary traffic control; and setup, maintenance, and  
6                   removal of all temporary traffic control devices and construction signs necessary  
7                   to control traffic during construction operations.

8                   **2.22.4.7.1           *Traffic Control Management***

9                   One or more of the Design-Builder's supervisors, who are actively involved in the  
10                  planning and management of field contract activities, shall assume the  
11                  responsibilities for traffic control management. The Design-Builder shall provide  
12                  the WSDOT Engineer with a copy of the formal assignment. The duties of traffic  
13                  control management shall not be Subcontracted.

14                  The Design-Builder's traffic control management personnel shall be responsible  
15                  for the following:

- 16                  1. Overseeing and approving the actions of the TCS to ensure that proper  
17                   safety and traffic control measures are implemented and consistent with the  
18                   specific requirements of the Project. An alternate form of oversight shall be  
19                   in place and effective when the traffic control management personnel are not  
20                   present at the Work area.
- 21                  2. Providing the Design-Builder's designated TCS with RFC TCPs which are  
22                   compatible with the Work and traffic control for which they will be  
23                   implemented.
- 24                  3. Discussing proposed traffic control measures and coordinating  
25                   implementation of the TCPs with the WSDOT Engineer.
- 26                  4. Coordinating all traffic control operations, including those of Subcontractors  
27                   and suppliers and the Toll Vendor, with each other and with any adjacent  
28                   construction or maintenance operations.
- 29                  5. Coordinating the Project's activities (such as ramp closures, road closures,  
30                   and lane closures) with appropriate police, fire control agencies, city or  
31                   county engineering, medical emergency agencies, school districts, and  
32                   transit companies.
- 33                  6. Overseeing all requirements of the Contract that contribute to the  
34                   convenience, safety, and orderly movement of vehicular and pedestrian  
35                   traffic.
- 36                  7. Reviewing the TCS's diaries daily and being aware of field traffic control  
37                   operations.
- 38                  8. Coordination, review, and retention of video log and storage.
- 39                  9. Have available at all times, on-site, all applicable standards and  
40                   specifications as described in this Section.

1       Failure to carry out any of the above-referenced responsibilities shall be  
2       considered a failure to comply with the Contract and may result in a suspension of  
3       Work as described in Section 1-08 of the *General Provisions*.

4                   **2.22.4.7.2      Traffic Control Supervisor**

5       The Design-Builder shall designate one or more people to perform the duties of  
6       the primary TCS and identify an alternate TCS who can assume the duties of the  
7       primary TCS in the event of that person's inability to perform. The TCS shall be  
8       responsible for safe implementation of the RFC TCPs.

9       TCS shall have at least 5 years of practical temporary traffic control experience  
10      with design and implementation of TCPs on freeway construction projects.

11      The TCS shall be certified as a State Traffic Control Supervisor by one of the  
12      following agencies:

13                   The Northwest Laborers-Employers Training Trust  
14                   27055 Ohio Avenue  
15                   Kingston, WA 98346  
16                   (360) 297-3035

17                   Evergreen Safety Council  
18                   12545 135th Avenue NE  
19                   Kirkland, WA 98034  
20                   (800) 521-0778 or (425) 814-3868

21                   American Traffic Safety Services Association  
22                   15 Riverside Parkway, Suite 100  
23                   Fredericksburg, VA 22406  
24                   (800) 272-8772 or (540) 368-1701

25                   Integrity Safety  
26                   13912 NE 20th Avenue  
27                   Vancouver, WA 98686  
28                   (360) 574-6607  
29                   <https://www.integritysafety.com>

30                   US Safety Alliance  
31                   (904) 705-5660  
32                   <https://www.ussafetyalliance.com>

33                   K&D Services  
34                   2719 Rockefeller Avenue  
35                   Everett, WA 98021  
36                   <https://www.kndservices.net/>

37      Possession of a current State flagging card by the TCS is mandatory.

38      A TCS shall be present on the Project whenever flagging, or other traffic control  
39      is occurring; or less frequently, as authorized by the WSDOT Engineer.

1 During nonworking hours, the TCS shall be on-site within 45 minutes after  
2 notification by the WSDOT Engineer.

3 The TCS shall perform all of the duties listed below:

- 4 1. Possess a current set of RFC TCPs; applicable Contract Provisions as  
5 provided by the Design-Builder; the *Washington State Modifications to the*  
6 *Manual on Uniform Traffic Control Devices*; the MUTCD; the ATSSA  
7 *Quality Guidelines for Work Zone Traffic Control Devices*; and applicable  
8 standards and specifications.
- 9 2. Inspect traffic control devices and nighttime lighting for proper location,  
10 installation, message, cleanliness, and effect on the traveling public. Traffic  
11 control devices shall be inspected at least once per hour during working  
12 hours, except that Class A signs and nighttime lighting may be inspected  
13 only twice a week. Traffic control devices left in place for 24 hours or more  
14 shall also be inspected once during nonworking hours when they are initially  
15 set up (during daylight or darkness, whichever is opposite of the working  
16 hours). The TCS shall correct, or arrange to have corrected, any deficiencies  
17 noted during these inspections.
- 18 3. Prepare a daily traffic control diary on each day that traffic control is  
19 performed using WSDOT Form 421-040A EF, *Contractor's Daily Report of*  
20 *Traffic Control - Summary* and WSDOT Form 421-040B EF *Contractor's*  
21 *Daily Report of Traffic Control - Traffic Control Log*. The Design-Builder  
22 shall maintain all copies of the daily traffic control diaries and shall make  
23 them available to the WSDOT Engineer no later than the end of the next  
24 business day. The Design-Builder may use alternate forms if approved by  
25 the WSDOT Engineer. Diary entries shall include, at a minimum, the  
26 following:
  - 27 a. Time of day when signs and traffic control devices are installed and  
28 removed
  - 29 b. Location and condition of signs and traffic control devices
  - 30 c. Revisions to the TCPs
  - 31 d. Lighting used at night
  - 32 e. Observations of traffic conditions
  - 33 f. Identify TCPs in use and provide location on the Project where TCPs are  
34 used
- 35 4. Make minor revisions to the TCPs to accommodate Site conditions and  
36 minimize obstructions, provided that the original intent of the TCPs is  
37 maintained. The revisions shall only shift devices laterally without adding or  
38 deleting devices and shall be documented in the daily traffic control diary.  
39 The TCPs shall be revised and re-released when determined necessary by  
40 the WTEM.
- 41 5. Attend traffic control coordination meetings or coordination activities,  
42 including meetings and activities for adjacent projects, as necessary, for a  
43 complete understanding of the Project and effective performance.

6. Ensure that all required traffic control devices and equipment are available and in good working condition prior to the need to install or use them.
  7. Ensuring that all pedestrian routes or access points, existing or temporary, are kept clear and free of obstructions and that all temporary pedestrian routes or access points are detectable and accessible to persons with disabilities as provided for in the RFC TCPs.
  8. Have available at all times, on-site, all applicable standards and specifications available as described in this Section.

Provided that the duties of the TCS are accomplished, the TCS may perform other duties described in this Section.

The TCS shall be considered a critical component of the Design-Builder's management team and shall have prior experience managing TCP operations on similarly complex projects. Registration as a Professional Engineer is not required; however, the Design-Builder may elect to use the WTEM in this position. The TCS shall attend all MOT task force meetings. The TCS shall also coordinate activities with the Communications Specialist.

The TCS or a designee shall be available on a 24-hour basis with a single contact phone number throughout the duration of the Project; supervise and verify all changes in the TCP setup; and perform daily Project Reviews to verify that traffic control devices are correctly placed and traffic is safely and efficiently moving through the Project. The TCS or an alternate TCS shall be on-site within 45 of notification of an emergency situation and shall be prepared to positively respond to the need to repair the traffic control system or to provide alternate traffic arrangements. The TCS shall have the resources, ability, and authority to expeditiously correct any deficiencies in the traffic control system, or to de-mobilize any construction operation that is resulting in excessive delays to traffic or creating an unsafe condition.

The TCS shall maintain a 30 Calendar Day advance schedule of all traffic control activities and a long-range schedule for all planned ramp and roadway closures. The TCS shall coordinate with the Design-Builder's Communications Specialist to ensure the information is disseminated to WSDOT, Local Agencies, and the public.

The TCS shall perform drive-through inspections as indicated above and immediately after any shift in TCP setup, while crews are still on-site to make modifications. If the Project has signalized intersections, the review shall be done prior to each morning peak traffic period, and each signal cycle shall be reviewed. At least two of the daily inspections each week shall be performed at night so that the arrangement and condition of the lights can be reviewed. The inspections shall also include assurances that pedestrians and bicyclists have a safe travel path around or through the Project area, and that existing businesses have adequate access during business hours, if applicable. The results of the inspections shall be documented in a daily report that, at a minimum, lists the time frame of the drive-through inspection and the defects noted. The report shall also document any maintenance or corrective action ordered as a result of the inspection, and the

1 name and position of the Design-Builder's personnel who have been directed to  
2 provide the maintenance or corrective action. The daily report shall state that the  
3 TCP setup and all traffic control devices substantially conform to the Contract  
4 requirements, except as noted, and shall be signed by the TCS.

5 **2.22.4.7.3 *Flaggers***

6 Workers engaged as flaggers shall wear reflective vests and hard hats. High-  
7 visibility apparel shall be in accordance with Section 1-07 of the *General*  
8 *Provisions*.

9 Flaggers shall be posted where shown on the RFC TCPs. All flaggers shall  
10 possess a current flagging card issued by the states of Washington, Oregon,  
11 Montana, or Idaho. The flagging card shall be immediately available and shown  
12 to the WSDOT Engineer upon request.

13 Flagging stations shall be shown on TCPs at locations where construction  
14 operations require stopping or diverting public traffic. Flagging stations shall be  
15 staffed only when flagging is required. This staffing may be continuous or  
16 intermittent, depending on the nature of the construction activity. Whenever a  
17 flagger is not required to stop or divert traffic, the flagger shall move away from  
18 the flagging station to a safer location.

19 During hours of darkness, flagging stations shall be illuminated in a manner that  
20 ensures that flaggers can be seen easily, but that does not cause glare to the  
21 traveling public. Flagger Station illumination shall meet the requirements of the  
22 MUTCD and this Section.

23 Flaggers shall be equipped with portable two-way radios, with a range suitable for  
24 the Project. The radios shall be capable of having direct contact with Project  
25 management (e.g., foremen and superintendents).

26 The Design-Builder shall provide portable lighting equipment capable of  
27 sufficiently illuminating a flagger and their station without creating glare for  
28 oncoming motorists yet will meet the mobility requirements of the operation. The  
29 lighting stations shall be located on the same side of the roadway as the flagger  
30 and aimed either parallel or perpendicular to the traveled lanes to minimize glare.  
31 The lighting devices shall be located 5 to 10 feet from the edge of the travel lane  
32 with a mounting height of 15 to 25 feet above the ground. The flagger shall be  
33 visible and discernable as a flagger from a distance of 1,000 feet.

34 The Design-Builder shall provide the standard stop/slow paddles for all flagging  
35 operations. Stop/slow paddles shall conform to the Standard Specifications.

36 No flaggers shall be used on freeways, ramps, and collector-distributor roadways.

37 **2.22.4.7.4 *WSDOT Electrical Inspector***

38 The Washington State Department of Labor and Industries has authority over all  
39 electrical installations within the State. WSDOT has been granted authority over  
40 all electrical installations within the Right of Way of State highways, provided  
41 WSDOT maintains and enforces an equal, higher, or better standard of

1 construction, materials, devices, appliances, and equipment than is required by  
2 Applicable Laws. It is the role of the WSDOT Electrical Inspector to ensure that  
3 all electrical installations, including Illumination, Traffic Signal, and ITS  
4 installations, meet the requirements of the National Electrical Code and  
5 Applicable Laws and provisions.

6 The WSDOT Electrical Inspector will perform the following:

- 7
- 8 • Act as a resource for the electrical design team
  - 9 • Assist with electrical system plan reviews (as applicable)
  - 10 • Perform periodic electrical inspections during construction
  - 11 • Witness required field tests (as desired)
  - 12 • Perform inspections required before energizing any new equipment or
  - 13 • Circuits
  - 14 • Inspect and approve all electrical installations in accordance with this
  - Contract

15 **2.22.4.7.5        *Other Traffic Control Labor***

16 In addition to flagging or spotting duties, the Design-Builder shall provide  
17 personnel for all other traffic control procedures required by the construction  
18 operations; and personnel to install, maintain, and remove any traffic control  
19 devices shown on the TCPs.

20 **2.22.4.8        *Video Record***

21 A drive-through video of all TCP devices shall be made each week, immediately  
22 after each collision causing injuries, and after each shift in TCP setup. The video  
23 recordings shall be saved digitally and maintained in a remote, fireproof location,  
24 and a log of the video recordings with dates and times shall be provided to the  
25 WSDOT Engineer on a monthly basis. The WSDOT Engineer shall have the right  
26 to review the video recordings at any time with 24 hours' notice to the  
27 Design-Builder.

28 **2.22.4.9        *Traffic Control Procedures***

29 **2.22.4.9.1        *One-Way Traffic Control***

30 The Work may require that traffic be maintained on a portion of the roadway  
31 using one-way traffic control. If this is the case, the Design-Builder's operation  
32 shall be confined to one-half of the roadway, permitting traffic on the other half.  
33 If shown on the RFC TCPs or as directed by WSDOT one-way traffic control  
34 shall be provided and shall also conform to the following requirements:

- 35
- 36 • In any one-way traffic control configuration, side roads and approaches  
37 shall be closed or controlled by a flagger or by appropriate signing. A  
38 side road flagger shall coordinate with end flaggers where there is line of  
sight and with the pilot car where the end flaggers cannot be seen.

- 1           • Queues of vehicles shall be allowed to take turns passing through the  
2           Work zone in the single open lane. When one-way traffic control is in  
3           effect, Design-Builder vehicles shall not use the open traffic lane except  
4           while following the same rules and routes required of the public traffic.

5           At the end of each Calendar Day the Design-Builder shall leave the Work area in  
6           such condition that it can be traveled without damage to the Work, without danger  
7           to traffic, and without one-way traffic control. If, in the opinion of the WSDOT  
8           Engineer, one-way traffic control cannot be dispensed with after working hours,  
9           then the operation shall be continued throughout the nonworking hours.

10           **2.22.4.9.2           *Rolling Slowdown***

11           When a short-term roadway closure of 15 minutes or less is needed for an  
12           infrequent, nonrepetitive Work operation such as traffic signal erection or utility  
13           wire crossing, the Design-Builder may implement a rolling slowdown on a multi-  
14           lane roadway, as part of an RFC TCP. Rolling slowdown traffic control  
15           operations shall not be used for routine Work that can be addressed by standard  
16           lane or shoulder closure traffic control. Rolling slowdowns on I-405 and SR 522  
17           will only be permitted between 12:01 a.m. and 4:00 a.m. on Monday, Tuesday,  
18           Wednesday, Thursday, and Friday. Rolling slowdowns will not be permitted to set  
19           girders or sign structure placement.

20           Where included in the RFC TCPs, a rolling slowdown shall be accomplished  
21           using one traffic control vehicle with flashing amber lights for each lane to be  
22           slowed down, plus one control vehicle to serve as a chase vehicle for traffic ahead  
23           of the blockade. The Design-Builder shall provide and pay for a minimum of two  
24           WSP officers per direction, for mainline rolling slowdowns. The traffic control  
25           vehicles shall enter the roadway and form a moving blockade to reduce traffic  
26           speeds and create a clear area in front of the moving blockade to accomplish the  
27           Work without a complete stoppage of traffic.

28           A PCMS shall be placed ahead of the starting point of the traffic control to warn  
29           traffic of the slowdown. The sign shall be placed far enough ahead of the Work to  
30           avoid any expected backup of vehicles.

31           The location where the traffic control vehicles begin the slowdown and the speed  
32           at which the moving blockade is allowed to travel shall be calculated by the  
33           Design-Builder to accommodate the estimated time needed for closure. The chase  
34           control vehicle shall follow the slowest vehicle ahead of the blockade. The  
35           Design-Builder shall not begin the Work operation until the chase vehicle passes  
36           the Work area. In the event that the Work operation is not completed when the  
37           moving blockade reaches the site, all Work, except the Work necessary to clear  
38           the roadway, shall cease immediately, and the roadway shall be cleared and re-  
39           opened as soon as possible.

40           All ramps and entrances to the roadway between the moving blockade and the  
41           Work operation shall be temporarily closed with traffic control vehicles. Radio  
42           communications between the Work operation and the moving blockade shall be

1 established and utilized to adjust the speed of the blockade to accommodate the  
2 closure time needed.

If more than one rolling slowdown occurs during the same period, the Design-Builder shall ensure that any queues originating from previous rolling slowdowns have fully dissipated.

### **2.22.4.9.3      *Lane Closure Setup/Takedown***

7 Where allowed by the Contract, shown on the RFC TCPs or directed by WSDOT,  
8 the Design-Builder shall establish traffic control measures to close one or more  
9 lanes of a multi-lane facility. When this is scheduled to occur, the Design-Builder  
10 shall adhere to the following sequence:

- Set up advance warning signs on the shoulder of the roadway opposite the lane to be closed.
  - Set up advance warning signs on the same shoulder as the lane to be closed.
  - Move a TA with arrow board into place at the beginning of the closure taper.
  - Place channelization devices to mark the taper and the length of the closure as shown on the RFC TCPs.
  - Once the lane is closed, the TA/arrow board combination may be replaced with an arrow board without attenuator.

If additional lanes are to be closed, this shall be done in sequence with previous lane closures, using the same sequence of activities. A TA with arrow board is required during the process of closing each additional lane and may be replaced with an arrow board without attenuator after the lane is closed. Each closed lane shall be marked with a separate arrow board at all times.

26 Traffic control for lane closures shall be removed in the reverse order of its  
27 installation.

#### **2.22.4.9.4      *Patrol and Maintain Traffic Control Measures***

When temporary traffic control measures are in place, the Design-Builder shall patrol and maintain these measures, at all times. The Work shall consist of resetting displaced devices; assuring visibility of all devices; cleaning and repairing where necessary; providing maintenance for all equipment, including replacing batteries and light bulbs, as well as keeping motorized and electronic items functioning; and adjusting the quantity and location of devices to respond to actual conditions, such as queue length, unanticipated traffic conflicts, and other areas where planned traffic control has proven ineffective.

37 This Work shall be performed by the Design-Builder, either by or under the  
38 direction of the TCS. Personnel, with vehicles, if necessary, shall be dispatched so  
39 that all traffic control can be reviewed at least once per hour during working  
40 hours, and at least once during each Calendar Day.

1                   **2.22.4.10      Traffic Control Devices**

2                   Traffic control devices are used to visually guide drivers through Work zones.  
3                   Signing, channelizing devices, arrow boards, and warning beacons all display a  
4                   message to the driver. Work zone credibility is established through the proper use  
5                   of these devices to send correct messages to drivers. Poor Work zone credibility  
6                   has a direct, negative impact on Work zone safety by causing driver confusion,  
7                   frustration, and disrespect, which results in an increased potential for accidents.

8                   All traffic control devices shall be removed from the Work Zone Clear Zone or  
9                   placed behind barrier or guardrail away from traffic when not in use. Traffic  
10                  safety drums, traffic cones, tubular markers or tall channelizing devices may  
11                  remain in the Work Zone Clear Zone if they can be placed off the paved shoulder.

12                  The Design-Builder shall locate traffic control devices so as not to block the  
13                  existing sidewalk to pedestrians, and to provide adequate space for wheelchairs.

14                  **2.22.4.10.1      *Construction Signs***

15                  All construction signs required by the RFC TCPs, as well as any other appropriate  
16                  signs directed by the WSDOT Engineer, shall be provided by the Design-Builder.  
17                  The Design-Builder shall provide the posts or supports, and erect and maintain the  
18                  signs in a clean, neat, and presentable condition until they are no longer required.  
19                  Post-mounted signs shall be installed as shown in the Standard Plans. Sign  
20                  attachment to posts shall conform to the applicable detail shown in the Standard  
21                  Plans. When the construction signs are no longer required, the Design-Builder  
22                  shall remove all signs, posts, and supports from the Project and they shall remain  
23                  the property of the Design-Builder.

24                  No passing zones on the existing roadway, if any, that are marked with paint  
25                  striping and where striping is anticipated to be destroyed by construction  
26                  operations shall be replaced by “Do Not Pass” and “Pass With Care” signs. The  
27                  Design-Builder shall furnish and install the signs and posts. The signs shall be  
28                  maintained by the Design-Builder until they are removed, or upon Physical  
29                  Completion. When the Project includes striping by the Design-Builder, the signs  
30                  and posts shall be removed by the Design-Builder when the no-passing zones are  
31                  re-established by striping. The signs and posts shall become the property of the  
32                  Design-Builder.

33                  All existing signs, new permanent signs installed as part of the Work, and  
34                  construction signs installed as part of the Work that are inappropriate for the  
35                  traffic configuration at a given time, shall be removed or covered in accordance  
36                  with Section 8-21.3(3) of the Standard Specification.

37                  Construction signs are divided into two classes. Class A construction signs are  
38                  those signs that remain in service throughout the construction or during a major  
39                  phase of the Work. They are mounted on posts, existing fixed structures, or  
40                  substantial supports of a semi-permanent nature. Class A signs shall be designated  
41                  as such on the RFC TCPs. “Do Not Pass” and “Pass With Care” signs are Class A  
42                  construction signs. Sign and support installation for Class A signs shall be in  
43                  accordance with the Contract or the Standard Plans. Class B construction signs

1 are those signs that are placed and removed daily, or are used for short durations,  
2 which may extend for 1 to 3 Calendar Days. They are mounted on portable or  
3 temporary mountings.

4 Class A construction signs mounted behind traffic barrels shall be mounted a  
5 minimum of 5 feet above the ground (ground to bottom of sign).

6 Where it is necessary to add weight to signs for stability, sandbags or other  
7 similar ballast may be used, but the top of ballast shall not be more than 4 inches  
8 above the Roadway surface and shall not interfere with the breakaway features of  
9 the device. The Design-Builder shall follow the manufacturer's recommendations  
10 for sign ballasting.

11 Signs, posts, or supports that are lost, stolen, damaged, destroyed, or which the  
12 WSDOT Engineer deems to be unacceptable while used on the Project, shall be  
13 replaced by the Design-Builder.

14 **2.22.4.10.2      *Sequential Arrow Signs***

15 Sequential arrow signs shall be shown on the TCPs either as a stand-alone unit  
16 without a TA or as a unit with a TA. When required, and as shown on the TCPs,  
17 the Design-Builder shall provide, operate, and maintain sequential arrow signs.

18 **2.22.4.10.3      *Portable Changeable Message Signs***

19 Refer to Appendix B for requirements.

20 **2.22.4.10.4      *Barricades***

21 Where shown on the RFC TCPs or when requested by the WSDOT Engineer, the  
22 Design-Builder shall furnish, install, and maintain barricades. Barricades shall be  
23 kept in acceptable condition, as defined in the *ATSSA Quality Guidelines for*  
24 *Work Zone Traffic Control Devices*.

25 Where it is necessary to add weight to barricades for stability, the Design-Builder  
26 shall follow the manufacturer's recommendations for sign ballasting.

27 **2.22.4.10.5      *Traffic Safety Drums***

28 Where shown on the RFC TCPs, or when requested by the WSDOT Engineer, the  
29 Design-Builder shall furnish, install, and maintain traffic safety drums.

30 The Design-Builder shall use wide angle prismatic retroreflective sheeting as  
31 specified in this Section or Type C steady-burning warning lights and Type III or  
32 Type IV reflective sheeting as described in Section 9-28.12 of the Standard  
33 Specifications. All traffic safety drums shall be the same type and shall be in  
34 accordance with Section 9-35.7 of the Standard Specifications with the exception  
35 that retroreflective bands fabricated from prismatic retroreflective sheeting is also  
36 permitted as noted below.

37 Used traffic safety drums may be utilized, provided all drums used on the Project  
38 are of essentially the same configuration and in acceptable condition, as defined

1       in the *ATSSA Quality Guidelines for Work Zone Traffic Control Devices*. Used  
2       traffic safety drums shall meet the requirements of this Section.

3       Traffic safety drums shall be designed to resist overturning by means of a  
4       weighted lower unit that shall separate from the drum when impacted by a  
5       vehicle.

6       Traffic safety drums shall be regularly maintained to ensure that they are clean  
7       and that the drum and reflective material are in good condition. When a drum has  
8       been damaged beyond usefulness, or provides inadequate reflectivity, a  
9       replacement drum shall be provided by the Design-Builder at no cost to WSDOT.

10      When the traffic safety drums are no longer required, they shall be removed from  
11     the Project and shall remain the property of the Design-Builder.

12      **2.22.4.10.6      *Traffic Cones***

13      Where shown on the RFC TCPs, or when requested by the WSDOT Engineer, the  
14     Design-Builder shall furnish, install, and maintain traffic cones. The  
15     Design-Builder shall not use traffic cones on State highways nor interstates.  
16     Traffic cones shall be kept in good repair and shall be removed immediately when  
17     directed by the WSDOT Engineer. Where wind or moving traffic frequently  
18     displaces cones, an effective method of stabilizing cones, such as stacking two  
19     together at each location, shall be employed.

20      **2.22.4.10.7      *Tubular Markers and Tall Channelizing Devices***

21      The Design-Builder shall not use tubular markers or tall channelizing devices on  
22     State highways nor interstates for temporary lane closures or temporary  
23     channelization, unless specifically requested in writing by the Design-Builder and  
24     approved by the WSDOT Engineer.

25      **2.22.4.10.8      *Warning Lights and Flashers***

26      The Design-Builder shall provide and maintain Type C steady-burning lights  
27     attached to all traffic safety drums used for lane closures or shifting tapers during  
28     hours of darkness in accordance with Sections 9-35.7 and 9-35.11 of the Standard  
29     Specifications.

30      **2.22.4.10.9      *Wide Angle Prismatic Retroreflective Sheeting***

31      The Design-builder shall provide and maintain orange traffic safety drums with  
32     two white and two fluorescent orange 6-inch-wide bands of wide angle prismatic  
33     retroreflective sheeting as specified below.

34      The wide angle prismatic retroreflective sheeting is sheeting with optimized  
35     performance at traditional observation angles and with extended entrance angle  
36     performance. The fluorescent orange sheeting shall be a visible activated  
37     fluorescent retroreflector providing higher daytime brightness than ordinary  
38     colored sheeting's of similar chromaticity. The white sheeting shall be a high  
39     brightness retroreflector providing higher brightness than non-prismatic  
40     sheeting's of similar chromaticity.

1       The retroreflector sheeting shall have a smooth surface with a distinctive  
2       interlocking diamond seal pattern visible from the face. The sheeting shall be  
3       precoated with a pressure sensitive adhesive backing protected by a removable  
4       liner.

## 2.22.4.10.9.1 Test Methods

6 Test Conditions: Unless otherwise specified herein, all applied and unapplied test  
7 samples and specimens shall be conditioned at the standard condition of 73°F  
8 (plus or minus 3°F) and 50 percent relative humidity (plus or minus 5 percent) for  
9 24 hours prior to testing.

10       Test Panels: Unless otherwise specified herein, when tests are to be performed  
11       using test panels, the specimens of retroreflective material shall be applied on  
12       smooth aluminum cut from ASTM B-209 Alloy 5052-H36.

## 2.22.4.10.9.2 Physical Requirements

14 The wide angle prismatic retroreflective sheeting shall meet the following  
15 physical requirements:

## Color

17 The color shall be in conformance to color requirements of Table I.

**Table I - Color specification limits for new sheeting (daytime)**

Color	Chromaticity Coordinate		Chromaticity Coordinate		Chromaticity Coordinate		Chromaticity Coordinate		Total Luminance Factor Limit, YT	
	1	2	3	4	min.	max.				
x	y	x	y	x	y	x	y			
White	.305	.305	.355	.355	.335	.375	.285	.325	40	--
Fluorescent Orange	.506	.404	.562	.350	.645	.355	.507	.429	30	-

## Fluorescence

19 The fluorescence shall be in conformance to fluorescence luminance factor  
20 requirements of Table II.

**Table II**

Sheeting Type	Fluorescence Luminance Factor Limit, YF Min.
Fluorescent Orange	15

Conformance to color and fluorescence requirements of Tables I and II shall be determined instrumentally on sheeting applied to aluminum test panels, using a 2-monochromator spectrophotometer employing annular 45/0 (or equivalent 0/45) illuminating and viewing geometry. The total chromaticity coordinates and total luminance factor shall be calculated from the total spectral radiance factors

1 computed for International Commission on Illumination (CIE) Illuminant D65 in  
2 accordance with ASTM E-308, *Practice for computing the colors of objects by*  
3 *using the CIE system* for the CIE 1931 (2 degrees) standard colorimetric observer.  
4 The measurement shall be made on a labsphere BFC-450 bispectral fluorescence  
5 colorimeter or equivalent.

## 6 Coefficient of Retroreflection, RA

The coefficients of retroreflection shall not be less than the minimum values specified in Table III according to the sheeting type. Testing shall be in accordance with ASTM E-810. The coefficients of retroreflection shall be specified in candelas per lux per square meter.

**Table III – Minimum Coefficient of Retroreflection  $R_A$   
(Candelas per lux per square meter)**

Observation Angles (degrees)	Entrance Angles (degrees)		
	-4	30	45
<b>White</b>			
<b>0.10</b>	1000	600	180
<b>0.20</b>	550	300	130
<b>0.50</b>	200	100	50
<b>1.00</b>	12	15	15
<b>Fluorescent Orange</b>			
<b>0.10</b>	375	200	50
<b>0.20</b>	200	120	40
<b>0.50</b>	80	50	30
<b>1.00</b>	10	10	10

## 11 Gloss

12 The retroreflective sheeting shall have an 85-degree specular gloss of not less than  
13 50 when tested in accordance with ASTM D-523.

14 **Flexibility**

15 The retroreflective sheeting with the liner removed and conditioned as in the test  
16 method described below shall be sufficiently flexible to show no cracking when  
17 slowly bent, in one second's time, around a 3.2-millimeter mandrel, with the  
18 adhesive contacting the mandrel, at test conditions. Talcum powder shall be  
19 spread on the adhesive to prevent sticking to the mandrel.

20 Adhesive

21 Protective liner attached to the adhesive shall be removable by peeling without  
22 soaking in water or other solutions and without breaking, tearing, or removing any

1 adhesive from the backing. Protective liner shall be easily removed following  
2 accelerated storage for 4 hours at 158°F under a weight of 2.5 pounds per square  
3 inch. The adhesive backing of the retroreflective sheeting shall produce a bond to  
4 support at 1.75-pound weight for 5 minutes without the bond peeling for a  
5 distance of more than 2 inches when applied to a test panel prepared in  
6 accordance with this Section. Apply 4 inches of a 1 by 6-inch specimen to a test  
7 panel. Condition and then position the panel face-down horizontally, suspend the  
8 weight from the free end of the sample, and allow it to hang free an angle of  
9 90 degrees to the panel surface for 5 minutes.

10 **Impact Resistance**

11 The retroreflective sheeting applied according to the sheeting manufacturer's  
12 recommendations to a test panel of alloy 6061-T6, 0.04 by 3 by 5 inches, and  
13 conditioned in accordance with this Section shall show no cracking outside the  
14 impact area when the face of the panel is subjected to an impact of 100 inch-  
15 pounds using a weight with a  $5/8$ -inch diameter rounded tip dropped from a height  
16 necessary to generate an impact of 100 inch-pounds, at test temperatures of both  
17 32°F and 72°F.

18 **Resistance to Accelerated Outdoor Weathering**

19 The retroreflective surface of the sheeting shall be weather resistant and show no  
20 appreciable cracking, blistering, crazing, or dimensional change after 1 year of  
21 unprotected outdoor exposure, facing the equator, and inclined 45 degrees from  
22 the vertical. Following weather exposure, panels shall be washed in a 5 percent  
23 HCL solution for 45 seconds, rinsed thoroughly with clean water, blotted with a  
24 soft, clean cloth, and brought to equilibrium at standard conditions. After  
25 cleaning, the coefficient of retroreflection shall not be less than 50 percent of the  
26 values in Table III when measured according to ASTM E 810. The color shall  
27 conform to the chromaticity coordinates of Table I, and the minimum  
28 fluorescence luminance factor  $Y_F$  shall not be less than 10. The sample shall:

- 29
- 30 • Show no appreciable evidence of cracking, scaling, pitting, blistering,  
edge lifting or curling, or more than  $1/32$ -inch shrinkage or expansion.
  - 31 • When more than one panel of a color is measured, the coefficient of  
retroreflection shall be the average of all determinations.
- 32

33 **Optical Stability**

34 Three pieces of new retroreflective sheeting applied test panels and conditioned in  
35 accordance with this Section shall each first have their photometric properties  
36 characterized by measuring the coefficients of retroreflection according to the  
37 provisions in this Section at all test geometries shown in Table III. These panels  
38 shall then be exposed in an air-circulating oven at 160°F (plus or minus 5°F) for a  
39 period of 24 hours. After exposure the panels shall be allowed to condition  
40 according to the provisions in this Section. These panels will again be  
41 characterized for photometric properties by measuring the coefficients of  
42 retroreflection according to the provisions of this Section at all test geometries  
43 measured before exposure. The coefficients of retroreflection measured after

1 exposure shall be between 80 percent and 120 percent of the values shown in  
2 Table III.

3 **Resistance to Corrosion**

4 The retroreflective sheeting applied to a test panel and conditioned in accordance  
5 with this Section shall show no loss of adhesion, appreciable discoloration or  
6 corrosion, and after cleaning shall retain a minimum of 80 percent of the  
7 specification minimum when measured at 0.2 degrees' observation, -4 degrees'  
8 entrance angle after 1,000 hours' exposure to a 5 percent concentration salt spray  
9 at 35 degrees when tested in accordance with ASTM B 117.

10 **General Characteristics**

11 The retroreflective sheeting applied to traffic control devices shall be free from  
12 ragged edges, cracks, and extraneous materials.

13 **2.22.4.10.10 *Transportable Attenuator***

14 Where shown on the RFC TCPs, or when requested by the WSDOT Engineer, the  
15 Design-Builder shall provide, operate, and maintain TAs. These TAs shall be  
16 available, on-site, for the entire duration of their anticipated use.

17 The TA shall be placed on each closed lane to separate and protect construction  
18 Work zone activities from normal traffic flow. During use, the attenuator shall be  
19 in the full down-and-locked position. For stationary operations, the truck's  
20 parking brake shall be set.

21 A TA may be used in lieu of a temporary impact attenuator as part of a stage  
22 traffic control shift to protect an object such as a blunt barrier end or a bridge pier  
23 column that is located within the WZCZ. This use of a TA is restricted to a  
24 maximum of 24 hours unless the WSDOT Engineer approves an extension.

25 **2.22.4.10.11 *Temporary Concrete Barrier***

26 Impact attenuators shall be used to protect the ends of barrier within the clear  
27 zone. Refer to Sections 6-10 and 8-17 of the Standard Specifications and Chapters  
28 1610, 1620, 1010, and 1030 of the WSDOT *Design Manual* for material and  
29 construction details regarding the barrier, glare screen, attenuators, and barrier  
30 delineators. Glare screen on TCB shall conform to the requirements of this  
31 Section and the Special Provisions.

32 **2.22.4.10.12 *Automated Flagger Assistance Device***

33 Refer to Appendix B for requirements.

34 **2.22.4.10.13 *Radar Speed Display Sign***

35 Refer to Appendix B for requirements.

36 **2.22.4.10.14 *Smart Work Zone System***

37 Refer to Appendix B for requirements.

1                   **2.22.4.10.15      Queue Warning System**

2                   Refer to Appendix B for requirements.

3                   **2.22.5      Submittals**

4                   TMP and TIMP require a draft and final submittal prior to commencement of any  
5                   construction activity that has the potential to impact traffic.

6                   TCPs for individual construction phases require a Preliminary Design Submittal  
7                   and a Final Design Submittal prior to approval for each phase of construction.

8                   **2.22.5.1      Transportation Management Plan**

9                   The Design-Builder shall submit an electronic copy of the draft TMP to WSDOT  
10                  for Review and Comment.

11                  The final TMP shall carry the WTEM's Professional Engineering stamp and  
12                  signature. The Design-Builder shall submit an electronic copy of the final TMP to  
13                  the WSDOT Engineer for Review and Comment. All comments to the TMP shall  
14                  be resolved prior to commencement of any construction activity that has the  
15                  potential to impact traffic. Changes to the TMP shall be prepared and submitted to  
16                  the WSDOT Engineer for Review and Comment 14 Calendar Days after the need  
17                  to change is recognized by the WSDOT Engineer or the Design-Builder.

18                  **2.22.5.2      Traffic Incident Management Plan**

19                  The Design-Builder shall submit an electronic copy of the draft TIMP to the  
20                  WSDOT Engineer for Review and Comment within 30 Calendar Days of NTP.

21                  The final TIMP shall carry the WTEM's Professional Engineering stamp and  
22                  signature. The Design-Builder shall submit an electronic copy of the final TIMP  
23                  to the WSDOT Engineer for Review and Comment. All comments to the TIMP  
24                  shall be resolved prior to commencement of any construction activity that has the  
25                  potential to impact traffic. Changes to the TIMP shall be prepared and submitted  
26                  to the WSDOT Engineer for Review and Comment 14 Calendar Days after the  
27                  need to change is recognized by the WSDOT Engineer or the Design-Builder.

28                  **2.22.5.3      Temporary Traffic Control Plans**

29                  The Design-Builder shall submit TCPs to the WSDOT Engineer for Review and  
30                  Comment prior to the Preliminary and Final Design Submittals. The  
31                  Design-Builder may submit TCPs separately for each phase of construction. The  
32                  TCPs shall meet minimum configurations as shown in Appendix T. The TCPs  
33                  must be distributed and RFC prior to implementation. All traffic control  
34                  implemented in the field shall be in accordance with RFC TCPs. The  
35                  Design-Builder shall consider the review times when planning for implementation  
36                  of construction phases. Reviews may only be waived or expedited with approval  
37                  from the WSDOT Engineer in emergency situations.

1        The Design-Builder shall prepare plan sheets in MicroStation format and in  
2        accordance with the Mandatory Standards and the WSDOT *Plans Preparation*  
3        *Manual*.

4        The Preliminary Design Submittal shall show lane configurations including  
5        typical cross-sections, signing, and Work zones. General notes to show the intent  
6        of the construction phase shall also be included. Stations and offsets of barriers,  
7        lane lines, edge lines, and tapers shall be included in the Preliminary Design  
8        Submittal. Stations and offsets of PCMS and signs are not required for the  
9        Preliminary Design Submittal. The Design-Builder shall submit one electronic  
10      copy of the TCPs to the WSDOT Engineer for Review and Comment.

11      The Final Design Submittal shall include, but is not limited to, all required details  
12      including station and offset for all elements, cross-sections, temporary drainage,  
13      pavement marking details, signing, traffic control devices, temporary or modified  
14      traffic signals, and temporary lighting. The Design-Builder shall submit one  
15      electronic copy of the TCPs to the WSDOT Engineer for Review and Comment.

16      When all comments from the Final Design Submittal TCPs have been resolved,  
17      the Design-Builder shall prepare RFC TCPs, carrying the stamp and signature of a  
18      Professional Engineer. For roadways outside of limited access, the Design-  
19      Builder shall submit TCPs for review and approval to the Local Agencies  
20      responsible for the roadway. The Design-Builder shall provide an informational  
21      copy of the submittal to the WSDOT Engineer. The Design-Builder shall allow a  
22      minimum of 14 Calendar Days for the Local Agencies to review the plans. If the  
23      plans are not approved, they shall be corrected and resubmitted until they are  
24      approved. Once approval is received and all requirements of the Quality  
25      Management Plan are satisfied, the plans may be RFC. The Design-Builder shall  
26      provide four sets of the approved RFC TCPs to the WSDOT Engineer prior to  
27      implementation.

28      The RFC TCPs shall be distributed to all stakeholders a minimum of 14 Calendar  
29      Days prior to implementation of any lane, ramp, sidewalk, or roadway closures or  
30      detours, in order to allow for public notification.

31      **2.22.5.4      Temporary Signal Plans**

32      Temporary Signal Plans shall be submitted to the WSDOT Engineer, the affected  
33      local agency, and the operating agency for Review and Comment prior to  
34      commencement of construction for temporary signals. Temporary Signal Plans  
35      shall be submitted as part of the TCPs packages for the phase in which they will  
36      be required.

37      **2.22.5.5      Temporary Illumination Plans**

38      Lighting level calculations, including electronic files, shall be submitted to the  
39      WSDOT Engineer for Review and Comment prior to planning any pavement  
40      marking changes. When the analysis shows temporary illumination is required,  
41      the Design-Builder shall submit Temporary Illumination Plans as part of the TCPs  
42      package for the stage in which the illumination will be required.

1                   **2.22.5.6       Temporary Drainage Calculations**

2                   Calculations for the design of temporary drainage facilities shall be submitted to  
3                   the WSDOT Engineer for Review and Comment with the TCPs Preliminary and  
4                   Final Design Submittals. When the drainage analysis shows temporary drainage is  
5                   required, the Design-Builder shall submit temporary drainage plans as part of the  
6                   TCPs package for the stage in which the drainage will be required. Temporary  
7                   drainage calculations shall meet the requirements in Section 2.14, *Stormwater*,  
8                   that apply to permanent drainage facilities.

9                   **2.22.5.7       Other Submittal Requirements**

10                  The Design-Builder shall deliver to the WSDOT Engineer a list of all parties  
11                  invited to take part in the MOT task force, and the responses to all of the  
12                  invitations. The Design-Builder shall take meeting minutes and distribute them to  
13                  all task force members.

14                  A copy of the MOT diary shall be submitted to the WSDOT Engineer monthly.  
15                  Upon Completion of the Project, the MOT diaries shall be delivered to the  
16                  WSDOT Engineer.

17                  A Closure Plan shall be submitted for each full highway closure. The  
18                  Design-Builder shall submit the Closure Plan to the WSDOT Engineer for  
19                  Review and Comment at least 60 Calendar Days prior to the scheduled closure.

20                  **2.22.5.8       Miscellaneous Submittals**

21                  At the request of the WSDOT Engineer, the Design-Builder shall deliver to the  
22                  WSDOT Engineer Work-related submittals that do not fit in the previous  
23                  categories but are prepared in accordance with this Section.

24                  **End of Section**